



OMEN'S SERVICE

COMPUTER SERVICE & HOME SECURITY



Каталог

Алармни & ПП Системи

Вашата безбедност е
Наша одговорност !



Ви нудиме

- ✓ Автоматика на врати
- ✓ Алармни системи
- ✓ Домофонија & Видеофонија
- ✓ Противпожарни системи
- ✓ Контрола на пристап
- ✓ Озвучување на објекти
- ✓ Кабли и напојување
- ✓ Компјутерски мрежи



078 841 602

Гаранција на производите е од 1-24 месеци.

Омен Сервис го задржува правото на промена на цените без претходна најава.

Wireless Alarm System DAHUA

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	DAHUA ART-ARC3000H-03-GW2(868) – Alarm KIT Supports 150 wireless peripherals Peripherals status display (signal strength, battery level, temperature, program version) Wired, Wi-Fi or GPRS network connection; Dual SIM and Single Standby, auto switching; Automatic network replenishment (ANR); Video linkage on App SOS emergency alarm; Frequency hopping function and two-way communication technology ensure communication stability;	
	ARD1233-W2 - Wireless PIR detector Pet immunity function; Auto temperature compensation; 3-level sensitivity adjustment; Low battery alarm; Anti-tampering; Temperature measurement; Frequency hopping function and two-way communication technology ensure communication stability;	
	DAHUA ARD1731-W2 Wireless PIR-Camera Maximum resolution 1600*1200; Based on the RF-HD image transmission technology, transmission of 6 HD images with resolution of 1600*1200 needs up to 10 seconds; One-week cloud cache for videos and images; Temperature monitoring;	
	ARD323-W2 - Wireless door detector Signal strength detection; Low battery alarm; Temperature measurement Frequency hopping function and two-way communication technology ensure communication stability; Cloud update and automatic recovery from update failure	
	ARA13-W2 - Wireless outdoor siren IP65 rated; Outdoor product (–25 °C to +60 °C); 12 VDC and battery power supply. · Multiple alarm sounds: Fire, medical, intrusion, panic, and more; Sound pressure level: 110 dB; Temperature monitoring; Frequency hopping and two-way communication;	
	ARA12-W2 - Wireless siren Signal strength detection; Low battery alarm; Temperature measurement; Frequency hopping function and two-way communication technology ensure communication stability; Cloud update and automatic recovery from update failure.	
	ARA24-W2 Wireless keyfob SOS emergency alarm; Frequency hopping function and two-way communication technology ensure communication stability;	
	ARK30T-W2 - Wireless Keypad Supports 3 shortcut alarms: Medical, fire, emergency; Arm/Disarm with password or IC card; Supports signal strength detection to select suitable installation sites; Low battery alarm; Temperature measurement; Frequency hopping function and two-way communication; Cloud update and automatic recovery from update failure.	
	ARD821-W2 - Wireless Panic Button Two-way RF communication; Provides multiple LED colors to indicate different statuses; Cloud update and automatic recovery from update failure; Offers accidental press prevention; Battery life up to 5 years if used twice a week; IP54 rated	
	ARM310-W2 - Wireless input expander Six types of alarm: intrusion, medical, fire, emergency, gas, and tamper; NC and NO are available for alarm inputs (NO by default); Signal strength detection; Low battery alarm; Temperature monitoring; Frequency hopping function and two-way communication technology ensure communication stability;	
	DAHUA ARD912-W2(868D) Wireless Water Leak Detector Frequency hopping and two-way communication technology ensure that communication is stable; Displays the temperature of the surrounding environment and supports the overheating alarm; Sensitivity adjustment;	

	ARA43-W2 - Alarm Repeater Connects up to 32 peripherals; Two-way RF communication; LED indicator displays device status; Supports auto pairing, extending RF distance for your security system; Auto switches from dual antennas to reduce blind area; Battery backs device working for over 35 hours	
	DAHUA HY-SA21A-W2(868) Wireless Smoke Alarm Split-spectrum sensor technology; Test and silence features in one single button; Loud sound output over 85 dB(A) at 3 meters; Low quiescent current consumption; Surface-mount device (SMD) circuit board design; Low battery warning signal	
	DAHUA HY-SAV849HA-E 5MP IR AI-fire Smoke Sensing Network Camera Remote check based on smoke sensing and video alarm linkage · Intelligent monitoring: Flame detection · With split-spectrum smoke chamber and intelligent algorithm, eliminate the false alarm effectively Built-in alarm voices, and user can import custom voices; 2/2 Alarm in/out, 1/1 audio in/out; supports max. 256 GB Micro SD card;	

Wireless Alarm System AJAX

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	AJAX Starter Kit White/Black Стартниот комплет за безбедносниот систем Ајакс. Комплетот се состои од хаб, детектор за движење, детектор за отворање и приврзок со паник копче	
	AJAX HUB - Централна единица White/Black Централна единица (HUB) за безжичен противпробивен систем со интегрирани LAN и GSM/GPRS комуникатори. Овозможено додавање и работа на до 100 безжични уреди, со до 50 корисници. Вградена back-up батерија. Бела боја	
	AJAX HUB2 - Централна единица White/Black	
	AJAX ReX - Засилувач за сигнал White/Black Безжичен рипитер на сигнал за AJAX системи, кој го појачува сигнало и до два пати, напојување 220VAC, вградена back-up Li-Ion 2A батерија (автономија и до 35 часа. Бела боја	
	AJAX MotionProtect - Безжична детекција на простор White/Black Безжичнафреквенција: 868Mhz; Безжичнакомуникација: Двонасочна; Вградување: Внатрешна; Метода надетекција: PIR; Неосетливостна домашнимиленици: <20kg, <50cm; Дострел надетекција: PIR: 12m; Дострел надетекција: MW: / ; Монтажа: Сидна; Степен насигурност: Grade 2;	
	AJAX MotionProtect Plus - Безжична детекција на простор White/Black Безжичнафреквенција: 868Mhz; Безжичнакомуникација: Двонасочна; Вградување: Внатрешна; Метода надетекција: PIR / MW; Неосетливостна домашнимиленици: <20kg, <50cm; Дострел надетекција: PIR: 12m; Дострел надетекција: MW: 12m ; Монтажа: Сидна; Степен насигурност: Grade 2;	
	AJAX CombiProtect - Безжична детекција на простор White/Black Безжичнафреквенција: 868Mhz; Безжичнакомуникација: Двонасочна; Вградување: Внатрешна; Метода надетекција: PIR / GB; Неосетливостна домашнимиленици: <20kg, <50cm; Дострел надетекција: PIR: 12m; Дострел надетекција: MW: / ; Монтажа: Сидна; Степен насигурност: Grade 2;	

	AJAX DoorProtect - Безжична детекција во точка White/Black Безжичен магнетен контакт со приклучок за дополнителен контакт.	
	AJAX DoorProtectPlus - Безжична детекција во точка White/Black Безжичнафреквенција: 868MHz; Безжичнакомуникација: Двонасочна; Вградување: Внатрешна; Детекција: Вибрации / Отворање - Затворање; Метода надетекција: Детектор на вибрации / Reed; Дострел надетекција: 20 mm; Монтажа: Надградна;	
	AJAX GlassProtect - Безжична детекција во точка White/Black Безжичен детектор за кршење на стакло со домет до 9m. Бела боја	
	AJAX HomeSiren - Безжични сирени White/Black Вградување: Внатрешна; Безжичнафреквенција: 868 MHz; Безжичнакомуникација: Двонасочна; Звучен излез: Прилагодливо, 81-105 dB @ 1m; Трепкачкосветло: LED; IP заштита: IP50;	
	AJAX StreetSiren - Безжични сирени White/Black Вградување: Надворешна; Безжичнафреквенција: 868 MHz; Безжичнакомуникација: Двонасочна; Звучен излез: Прилагодливо, 85-113 dB @ 1m; Трепкачкосветло: LED; IP заштита: IP54;	
	AJAX MotionProtect Outdoor - Безжична детекција на простор Безжичнафреквенција: 868MHz; Безжичнакомуникација: Двонасочна; Вградување: Надворешна; Метода надетекција: PIR / AM; Неосетливостна домашнимиленици: <80cm; Дострел надетекција: PIR: 15m; Дострел надетекција: MW: / ; Монтажа: Сидна / Столбна; Степен насигурност: Grade 2;	
	AJAX MotionCam WH	
	AJAX Keypad - Безжична тастатури White/Black Начин напреказ: Touchsense LED; Безжичнафреквенција: 868 MHz; Безжичнакомуникација: Двонасочна;	
	AJAX SpaceControl - Далечински управувач White/Black Безжичен далечински управувач, 4 функциски копчиња, LED известување. Бела боја	
	AJAX FireProtect - Безжична детекција на состојбата на околината Безжичнафреквенција: 868MHz; Безжичнакомуникација: Двонасочна; Вградување: Внатрешна; Детекција: Чад / температура / нагло растење натемпературата; Монтажа: Таванска; Степен насигурност: Grade 2 (EN50131-1);	
	AJAX FireProtect Plus - Безжична детекција на состојбата на околината Безжичнафреквенција: 868MHz; Безжичнакомуникација: Двонасочна; Вградување: Внатрешна; Детекција: Чад / CO / температура / нагло растење натемпературата; Монтажа: Таванска; Степен насигурност: Grade 2 (EN50131-1);	

	AJAX LeaksProtect - Безжична детекција на состојбата на околината Безжичнафреквенција: 868MHz; Безжичнакомуникација: Двонасочна; Вградување: Внатрешна; Детекција: Поплава; Монтажа: Таванска; Степен насигурност: Grade 2 (EN50131-1);	
	Ajax Transmitter - Влезен модул Модул за безжично поврзување на универзални безжични детектори (Optex BX80R, AMC Soutdoor BC и слично) на AJAX противпровалните системи.	
	AJAX MultiTransmitter WH	
	AJAX Socket WH / AJAX Socket BL - Безжични излезни модули Намена: Приклучок за 220VAC потрошувачи, Schuko-тип F; Безжичнафреквенција: 868 MHz;	
	AJAX WallSwitch BL - Безжични излезни модули Намена: Приклучок за 220VAC потрошувач; Безжичнафреквенција: 868 MHz;	
	AJAX Relay BL - Безжични излезни модули Намена: Релеен излез; Безжичнафреквенција: 868 MHz;	
	AJAX ocBridge Plus - Безжични модули Намена; Безжичнафреквенција: 868 MHz; Компатибилни централи: Жичани алармни централи; Спојување на алармната централа: Релеи; Број на PGM-и – жичано: 8; Број на зони - Безжично: 99;	
	AJAX uartBridge - Безжични модули Намена; Безжичнафреквенција: 868 MHz; Компатибилни централи: Жичани алармни централи; Спојување на алармната централа: UART; Број на PGM-и – жичано: /; Број на зони - Безжично: 99;	

Keypad Paradox

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	Paradox keypad K636 10-zone LED display; Compatible with E55, MG5000, MG5050 and Spectra SP series; Single partition keypad; StayD status LED; Patented Key Light display (button lights up to indicate an open zone); Arm, Sleep, Stay and Off keys illuminate to indicate partition status; Adjustable backlight	
	Paradox keypad K10 H/V 10-zone LED display; Compatible with MG5000, MG5050 and Spectra SP series; Supports StayD Mode; Separate Arm, Sleep, Stay and Off LEDs per partition; Patented Key Light display (button lights up to indicate an open zone); 1 keypad zone input; Independently set chime zones; 7 one-touch action buttons; 3 keypad-activated panic alarms; Adjustable backlight; Connects to 4-wire communication bus	
	Paradox keypad K32LED 32-zone LED display; Compatible with MG5000, MG5050 and Spectra SP series; Supports StayD Mode; Separate Arm, Sleep, Stay and Off LEDs per partition; In-field firmware upgrade via 307USB and WinLoad; 1 keypad zone input; Independently set chime zones; 7 one-touch action buttons; 3 keypad-activated panic alarms; Adjustable backlight; Connects to 4-wire communication bus	
	Paradox keypad K32LX 32-character blue LCD with programmable labels; Real-time zone alarm display (until disarmed); In-field firmware upgrade via 307USB and WinLoad; StayD status LED; 1 keypad zone input; 8 one-touch action buttons; 3 keypad-activated panic alarms; Adjustable backlight, contrast and scroll speed; Connects to 4-wire expansion bus; Compatible with MG5000, MG5050 and Spectra SP series V2.31 and up;	
	Paradox keypad K38 Wireless Powered by 2 "AA" batteries, with built-in backup battery (PA6 is optional), A 6Vdc power adaptor (PA6 not included) is not required but can be used as an alternative power source, 3 keypad-activated panic alarms, Built-in transceiver (433MHz), Compatible with MG6250, MG5000 / MG5050 V3.22, MG5075, Spectra SP V3.22 (except SP4000) and RTX3 V1.42	
	Paradox Interactive Touchscreen TM50 12.7 cm vivid color display (480 x 272 pixels); Intuitive, icon-based menus – no manual needed; Control up to 8 PGM outputs; In-field firmware upgradable via micro SD card; 1 zone/temperature input to connect a detection device or aTEMP07 (External Temperature Sensor); Customized translation via webapplication;	
	Paradox Interactive Touchscreen TM70 12.7 cm vivid color display (480 x 272 pixels); Intuitive, icon-based menus – no manual needed; Control up to 8 PGM outputs; In-field firmware upgradable via micro SD card; 1 zone/temperature input to connect a detection device or aTEMP07 (External Temperature Sensor); Customized translation via webapplication;	
	Power Adapter Plug PA6 For the K32RF and K32WK; Provides 6Vdc at 350mA max	

Wired Motion Detector PARADOX

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	Paradox 476 PRO+ Analog Single-Optic PIR; 11m x 11m and up to 15m for center beams with 88.5° viewing angle; Extremely high EMI and RFI rejection; PCB uses only surface mount components; Solid-state relay; Patented Auto Pulse Signal Processing; Automatic Temperature Compensation; Metal shield maximizes protection from EMI and RFI signals;	
	Paradox 476 PET P2C Analog Single-Optic PIR; Immune to animals weighing up to 18kg; 11m x 11m and up to 15m for center beams with 88.5° viewing angle; Extremely high EMI and RFI rejection; PCB uses only surface mount components; Solid-state relay Automatic Temperature Compensation; Metal shield maximizes protection from EMI and RFI signals;	
	Paradox NV5 High-Performance Infrared Motion Detector; Infrared motion detector managed by Full Authority Digital Electronics Control (FADEC); Paradox's Hybrid Cylindrical-Spherical 1.0" lens with 3rd generation 3D Lodiff® Fresnel segments- (10 x 10 m), 102° viewing angle, and 0.5 m to max range	
	Paradox DG85 Outdoor High-Security Digital Motion Detector; Impact and temperature resistant casing (-35°C to 50°C); Patented Digital Motion Detection; Extremely reliable and false-alarm free; Dual Optical Filtering System; UV protected lens; Dual optics (2 dual opposed element sensors); Digital Dual Opposed Detection; Multi-level sensitivity adjustment; Two operational modes (Bus or Relay operation)	/
	Paradox DG 457 Glassbreak Detector; Conventional solid-state relay operation; Full audio and infrasonic spectrum analysis; 7 frequency digital filters, digital amplifier gain and frequency fluctuation assessment; Impact and shock wave analysis; High-immunity to RFI and EMI signals; Adjustable sensitivity: covers up to 9m when set to high and up to 4.5m when set to low; Anti-tamper switch	
	Paradox DG467 360° Ceiling Mounted Digital Motion Detector; Two operational modes (addressable for the Digiplex and Digiplex EVO series or conventional relay operation); Dual opposed element sensor; Digital Detection; 7m x 6m at 2.4m; 11m x 6m at 3.7m; 360° viewing angle	/

Wireless Motion Detector PARADOX

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	Paradox PMD2P Wireless Analog Single-Optic PIR (433MHz); Dual element sensor; Immune to animals weighing up to 18kg; 11m x 11m and up to 15m for center beams with 88.5° viewing angle; Wireless range in a typical residential environment: 35m with MG6160, MG6130; 70m with MG5000, MG5050 and RTX3; Patented Auto Pulse Signal Processing; Automatic Temperature Compensation;	
	Paradox G550 Wireless Glassbreak Detector (433MHz); 6m radius range and 360° coverage pattern protects an entire room with one sensor; Detect breaking of different types of glass including plate, tempered, laminated and wired; Standard Alkaline 3x AAA type battery with low battery supervision; Factory-set sensitivity for safer installation; Recognizes actual pattern of breaking glass across the full audio band;	
	Paradox PMD85 Wireless Outdoor Digital Dual-Optic PIR (433MHz); Impact and temperature resistant casing; Operates at -35°C to +50°C; UV protected lens; Dual Optical Filtering System; Multi-level sensitivity adjustment, Patented Digital Motion Detection; Dual optics (2 dual opposed element sensors).	

Remote Control & Wireless Door Contacts

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	Paradox REM1 Remote Control with Backlit Buttons (433MHz); Water resistant; Perform up to 5 different actions; Wireless range in a typical residential environment:; 30m with all-in-one consoles and RX1; 45m with MG5000 / MG5050; 60m with RTX3	
	Paradox REM1 Emergency/Panic Remote Control (433MHz); Water resistant; Panic function allows user to instantly send panic signal to monitoring station; Includes lanyard attachment to facilitate portability; optional wrist strap and belt clip Includes easily-replaceable CR2032 battery, with a battery life of 3 years with MG6130 / MG6160 / MG6250 and RX1; 45m with MG5000 / MG5050, K32LX and K641LX; 60m with RTX3	
	PARADOX Metal Box 28cm X 28 X 8 cm; Provision for multiple module and panel mounting; Many punch-out holes for simple wiring; Easy door removal	

GSM Home Alarm System

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	M-WG107T Tuya Smart WiFi GSM Alarm System ◆ APP name: TuyaSmart; ◆ Work with Amazon Alexa/Google Assistance ◆ 4.3 inch touch screen LCD; ◆ Input Voltage: 5V/1A ◆ Support 100 wireless detector, remote control and RFID cards; ◆ Low-battery detection/Power off detection ◆ Built in battery to enable the alarm panel continue work when no WiFi;	
	M-WSR201 Wireless Signal Repeater with Adapter It is a special device for extending the wireless signals; Working voltage: DC12V; Operating current: 150mA-180mA; Distance extend 500-1000m;	

INFRARED BALUSTER or BEAMS

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	MT-20L Senzor Photo cell	
	IB705 3-beam,wired,Detecting distance: 250M; length:27CM	
	IB805 4-beam,wired,Detecting distance: 250M; length:35CM	
	IB110 Wireless- wired :twin-beam,outdoor detecting distance:40M,valid length:28cm	

INFRARED BALUSTER or BEAMS

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
	Sirena MS102 Wired siren, It directly connects to the main host;OPERATION VOLTAGE:DC6-12V; SOUND TYPE:SINGLE TONE/6-TONE; COLOR:BLACK/WHITE/RED; SIZE:54(W)×48(L)×54(H) mm	/
	S103 Outdoor - Indoor Wired Sound Horn rated voltage: DC12V; rated current: 1200mA; sound level: 115dB; power: 20W	
	M-CA-210 Outdoor - Indoor Wired Sound Horn Power supply:DC12V; Alarm current:600-1000mA; Alarm Sound:≥120dB;; Dimension: 300*300*200mm; Tones: single tone; Fire-proof ABS or PC material available	
	M-CA-600S Outdoor - Indoor Wired - Sound Horn 6 Tones Black Alarm Power supply:12V Operating; Voltage:6-15VDC; Rated Current: 600/1200 mA; Tones :6 Tones- Single Power: 15W/20W SPL (Db/m)	
	Blinking Rotary signal lamp High bright, High transparency fadeless, low noise, bolt fastening Magnetic solution Environmentally friendly and power saving. Good vibration resistance and stable emitting. Durable and non-fading brilliant beams. Instant and immediate light on. Voltage:DC12V. Long life:50000 hours or more. Waterproof, surge protection	
	Red LED Lamp Flashing Light	
	Siren FS-106 Wired Flashing & Sound Siren	
	Siren CA-102 flashing warning strobe & sound siren rated voltage: DC12V/24VDC/110V-220AC; rated current: 300mA; sound level: 120dB; power: 30W/40W; Strobe source: Xenon Tube/Led; flash frequency:70-90time/min	

	Siren HC-36A OPERATION VOLTAGE:DC 6-12V; SOUND TYPE:SINGLE TONE/6-TONE; OUTPUT POWER:10W/15W; COLOR:WHITE; SIZE:110(W)×55(L)×110(H)mm	
	Siren SL-350 Rated Voltage: DC12V ; Operating Voltage: DC9-15V ; Rated Current: 300mA ; Strobe source: Xenon Tube/LED ; Flash Frequency: 70-90 times/minute ; Sound SPL: 110dB ; Operating temperature: -20~60°C	
	Siren M-OFS-WG Wireless Outdoor Flash & Sound Siren with Backup Battery Note: only working for models: WG103, WG106, WG103T, WG107T; G30, G12. Note: Adapter included with tamper switch	
	Siren M-WG107T Wireless Outdoor Solar Siren working with PST-WG107T	
	Siren PA-200 Outdoor siren with flash, 120dB (without battery) INSIDE METAL COVER FOR DOUBLE PROTECTION; MAGNETIC DYNAMIC SOUNDERS WITH 120DB AT 1M; LEN CORLORS IN RED,BLUE,ORANGE,WHITE; 3 WAY TAMPER SWITCH PROTECTION	
	Siren SL-650R OUTER SIREN WITH STROBE LIGHT 24V Siren Voltage DC24v , Power 50W,Siren Current 1200mA , Strobe current 250mA ,Strobe freq 120-150/minute , SPL 128dB ,Lens color REDMaterial ABS/AS/PC	
	Paradox SR250 Wireless Siren with Built-in Strobe (433MHz); Compatible with MG Series V4.0 and SP series V4.0 whenusing an RTX3 V1.5; 100db wireless siren with integrated strobe light; Weather-resistant design using a PC/ABS enclosure with UVprotection and a silicone coated PCB (-20°C to 50°C); Battery powered only, no need for AC power; Wireless range in a typical residential environment:- 35m with MG6160, MG6130, and MG6250; 70m with MG5000, MG5050 and RTX3-2.5 hour alarm display (strobe flashes every 4 seconds afterbell cut-off);	
	M-ST-DC1 WIFI Smart Door Opener Relay; APP name:TuyaSmart; Work with Amazon Alexa/Google Assistance/IFTTT; Work Voltage: DC7-32V; Wifi Frequency: 2.4GHz; Relay Load: 250V/10A; Work alone, not work with alarm panel together	
	RTU5024 GSM Door Opener GSM Frequency , Quad-band 850/900/1800/1900MHz , Digital Output , NC/NO dry contact 3A/240VAC , Power consumption , 12V input Max. 50m A/Average 25mA , SIM Card Supporting 3V SIM Card, Temperature range -20~+60 °C, Backup battery 3.7V/900Mah; Exterior dimension 102mm*D76mm*H27mm	
	TTT603 GSM telephone modem GSM Dual Band, Compatible with GSM 900 /1800 MHZnetworks . Built-in Digital antenna; send and receive voice call, send and receive SMS, Interrogate your voicemail; Voice and SMS service; Information at a glance status LEDs, a new voice mailmessages and other important functions; Ring voltage: 68V; Power Supply: DC12V	
	TTT603 GSM telephone modem – With Battery GSM Dual Band, Compatible with GSM 900 /1800 MHZnetworks . Built-in Digital antenna; send and receive voice call, send and receive SMS, Interrogate your voicemail; Voice and SMS service; Information at a glance status LEDs, a new voice mailmessages and other important functions; Ring voltage: 68V; Power Supply: DC12V	/

	Paradox GPRS14 Communication Plug-in Module; Accessory for the MG6250, used to support GPRS/GSM/SMS reporting; Supports 2 standard GSM provider SIM cards, for provider redundancy; Simple installation; connects directly onto PCB	
	<u>Akumulator 12V - 1,3 Ah, dimenzii: 97 x 43 x 52mm (L x W x H), tezina 0.58kg</u> <u>Akumulator 12V - 4,0 Ah, dimenzii: 90 x 70 x 101mm (L x W x H), tezina 1.40kg</u> <u>Akumulator 12V - 7,0 Ah, dimenzii: 151 x 65 x 93.4mm (L x W x H), tezina 2.05kg</u>	
	Transformator 220VAC/16V-30VA vo zastitno kukiste so klemi I osiguruvac Transformator 220VAC/16.5V-45VA vo zastitno kukiste so klemi I osiguruvac	
	PC1520 stabilizirano napojuvanje 6/12VDC-1.5A polnac za akumulatorski baterii	
	PC3020 Stabilizirano napojuvanje 6/12VDC-3A polnac za akumulatorski baterii	
	Rele 12V	