

## IPC 8MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.8213	<b>DAHUA IPC-HDW2831T-AS-S2 2.8mm</b> <b>8MP Lite IR Fixed-focal Eyeball Network Camera</b> 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition; H.265 codec,; Built-in IR LED, max IR distance: 30 m; ROI, SMART H.264+/H.265+, flexible coding; 256 GB Micro SD card, built-in MIC; 12V DC/PoE ; IP67;	
 Ш.8214	<b>DAHUA HDBW2841R-ZAS</b> <b>8MP IR Vari-focal Dome WizSense Network Camera</b> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, and the max. illumination distance is 40 m; ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments;	
 Ш.8215	<b>DAHUA IPC-HDBW2841E-S</b> <b>8MP IR Fixed-focal Dome WizSense Network Camera</b> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps; Built-in IR LED, and the max. illumination distance is 30 m;	
 Ш.8216	<b>DAHUA IPC-HFW2831S-S-S2</b> <b>8MP Lite IR Fixed-focal Bullet Network Camera</b> 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, max IR distance: 30 m; 12V DC/PoE power support; IP67 protection	
 Ш.8217	<b>IPC-HFW2831T-AS-S2 3.6mm</b> <b>8MP Lite IR Fixed-focal Bullet Network Camera</b> 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, max IR distance: 80 m; Intelligent detection: Intrusion, tripwire; Alarm: 1 in, 1 out;	
 Ш.8218	<b>DAHUA IPC-HFW2841T-AS</b> <b>8MP IR Fixed-focal Bullet WizSense Network Camera</b> Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520@25/30 fps.Built-in IR LED, and the max. illumination distance is 80 m; Alarm: 1 in, 1 out ; audio: 1 in, 1 out ; Supports max. 256 G Micro SD card; built in MIC.	
 Ш.8219	<b>DAHUA IPC-HFW2841T-ZAS</b> <b>8MP IR Vari-focal Bullet WizSense Network Camera</b> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Built-in IR LED, and the max. illumination distance is 60 m. Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.	
 Ш.8220	<b>DAHUA IPC-HFW2831TP-ZS – Lite Series</b> <b>8MP WDR IR Bullet Network Camera</b> 1/1.8" 8Megapixel progressive CMOS; H.265 & H.264 dual-stream encoding 25/30fps@8MP(3840×2160); WDR(120dB), Micro SD card slot, up to 128GB; 3.7~11mm motorized lens; Max IR LEDs Length 60m; IP67, IK10(optional), PoE	
 Ш.8221	<b>DAHUA IPC-HFW3849T1-AS-PV-S3</b> <b>8MP Smart Dual Illumination Active Deterrence Bullet Camera</b> 8MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160)@25/30 fps.; Built-in warm light and IR LED; the max. IR illumination distance is 30 m and warm light distance is 30 ml Alarm: 1 in, 1 out; audio: 1 in, 1 out;	

## IPC 8MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.8210	<b>DAHUA IPC-HFW2849S-S-IL</b> <b>8MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera</b> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps; Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m;	
 Ш.8211	<b>DAHUA IPC-HDW2849TM-S-IL</b> <b>8MP Smart Dual Light Fixed-focal Eyeball WizSense Network Camera</b> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps; Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m;	
 Ш.8212	<b>DAHUA IPC-HFW2849T-AS-IL</b> <b>8MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera</b> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP @20 fps, and supports 2688×1520 @25/30 fps; Built-in warm light and IR LED, IR light distance is 60 m and max. warm light is 50 m;	