



OMEN'S SERVICE
COMPUTER SERVICE & HOME SECURITY

Каталог

Видео Надзор

Вашата безбедност е
Наша одговорност !



Ви нудиме

- ✓ Автоматика на врати
- ✓ Алармни системи
- ✓ Домофонија и видеофонија
- ✓ Противпожарни системи
- ✓ Контрола на пристап
- ✓ Озвучување на објекти
- ✓ Кабли и напојување
- ✓ Компјутерски мрежи



078 841 602

Гаранција на производите е 12 – 24 месеци.

Омен Сервис го задржува правото на промена на цените без претходна најава.

HDCVI 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.2340	DAHUA HAC-T1A21-U – 2.8mm 2MP HDCVI IR Eyeball Camera Max. 30 fps@1080p; Smart IR Illumination; 25 m illumination distance; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable;	
 Ш.2342	DAHUA HAC-HDW1200T-Z-A 2MP HDCVI IR Eyeball Camera Max 30fps@1080P; HD and SD output switchable; Built-in mic; 2.7-12mm motorized lens; Max. IR length 60m, Smart IR; IP67, DC12V	
 Ш.2343	DAHUA HUM1220G-B - 2.8mm 2MP HDCVI Bullet Camera Max 30fps@1080P, 2.8mm fixed lens,DC12V; HD and SD output switchable;	
 Ш.2344	DAHUA HAC-HUM3200A 2MP IR HDCVI Fixed-focal Cube Camera Max 30 fps@1080p; 10 m illumination distance (940nm IR No IR Exposure); Super Adapt; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable; 12 VDC;	
 Ш.2345	DAHUA HAC-B1A21 – 3.6mm 2MP HDCVI IR Bullet Camera Max. 30 fps@1080p; CVI/CVBS/AHD/TVI switchable; 3.6 mm fixed lens; Max. IR length 20 m, Smart IR; IP67,12 VDC;	
 Ш.2346	DAHUA HAC-B2A21 2MP HDCVI Fixed-focal Bullet Camera Max. 30 fps@1080p; Smart IR Illumination; 20 m illumination distance; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	
 Ш.2348	DAHUA HAC-HFW1231TM-I8-A – 3.6mm 2MP Starlight HDCVI IR Bullet Camera Max 30 fps@1080p; Starlight, 130 dB true WDR, 3D NR; 3.6 mm fixed lens; Super Adapt; Built-in mic; Max. IR length 80 m, Smart IR; IP67, DC 12 V;	
 Ш.2349	DAHUA LC1220T-TH - IoT Series - 2.8mm 2MP HDCVI Temperature & Humidity Camera Max 30fps@1080P, 2.8mm fixed lens, Max. IR length 20m, Detection range: - 40°C~60°C, 10-95% RH, Smart IR, IP67, DC12V	

HDCVI 2MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.2350	DAHUA HAC-HDW1200TLM-IL-A 2MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic; 2.8 mm fixed lens; IP67, 12 VDC;	
 Ш.2351	DAHUA HAC-HFW1200CM-IL-A 2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic; 2.8 mm fixed lens; IP67, 12 VDC;	
 Ш.2352	DAHUA HAC-HDW1200CLQ-IL-A – 2.8mm 2MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic; 2.8 mm fixed lens ; CVI/CVBS/AHD/TVI switchable; 12 VDC.	
 Ш.2354	DAHUA HAC-HFW1200TLM-IL-A - 2.8mm 2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera Max. 30 fps@1080p; 3D NR; Smart Dual Light; 40m illumination distance; Super Adapt; Built-in mic; 2.8mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12VDC	

HDCVI 2MP Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.2355	DAHUA HAC-HDW1209TLQ-A-LED - 2.8mm 2MP Full-color HDCVI Quick-to-install Eyeball Camera 24/7 color imaging; 20 m illumination distance; Max. 30 fps@1080p; Built-in mic; CVI/CVBS/AHD/TVI switchable; IP67, 12V±30% DC;	
 Ш.2356	DAHUA HAC-HFW1209C-LED - 2.8mm 2MP Full-color HDCVI Bullet Camera 24/7 color imaging; 20m illumination distance; Max. 30 fps@1080p; CVI/CVBS/AHD/TVI switchable; IP67, 12V±30% DC;	
 Ш.2357	DAHUA HAC-HDW1239T-A-LED 2.8mm with Audio 2MP Full-color HDCVI Eyeball Camera 24/7 color imaging, Max. 30 fps@1080p; 40 m illumination distance; Super Adapt, 130 dB true WDR, 3D NR; CVI/CVBS/AHD/TVI switchable; IP67, DC 12 V;	



HDCVI 5MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.5351	DAHUA HAC-HFW1500C - 3.6mm 5MP Starlight HDCVI IR Bullet Camera Max 25 fps@5MP; CVI/CVBS/AHD/TVI switchable; 2.8 mm fixed lens; Max. IR length 30 m, Smart IR; IP67, 12V DC;	
 Ш.5352	DAHUA HAC-B1A51-U 5MP IR HDCVI Fixed-focal Bullet Camera Max 25 fps@5MP (16:9 video output); Smart IR Illumination; 30 m illumination distance; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable. · IP67, 12 VDC.	
 Ш.5353	DAHUA HAC-EW2501 5MP HDCVI IR-Fisheye Camera 1/2.8" 5Megapixel progressive scan CMOS; Panoramic fisheye lens; Max. 20fps@5MP; Built-in Mic; 120dbtrue WDR, Starlight, 2D&3D NR; Max. IR length 10m,Smart IR;DC12V	
 Ш.5354	DAHUA HAC-T1A51-U 5MP IR HDCVI Fixed-focal Eyeball Camera Max 25 fps@5MP (16:9 video output); Smart IR Illumination; 25 m illumination distance; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable;	
 Ш.5301	DAHUA HAC-HDW1500TRQ-A - 2.8mm 5MP Starlight HDCVI Quick-to-install IR Eyeball Camera Max 25 fps@5MP (16:9 video output); Built-in mic (-A); CVI/CVBS/AHD/TVI switchable; 2.8 mm fixed lens; Max. IR length 25M; Smart IR; IP50, DC12V;	
 Ш.5354	UTC Controller PFM820 Support different formats (HDCVI/AHD/HDTVI/CVBS) switch, which ito satisfy the requirements of different storage device environments for clients;	

HDCVI 5MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.5355	DAHUA HAC-HDW1500CLQ-IL-A 2.8mm 5MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera Max 25 fps@5MP (16:9 video output); Smart Dual Light; 20m illumination distance; Super Adapt; Built-in MIC; CVI/CVBS/AHD/TVI switchable; IP67,12 VDC	
 Ш.5356	DAHUA HAC-HFW1500CL-IL-A - 3.6mm 5MP Smart Dual Light HDCVI Fixed-focal Bullet Camera Max 25 fps@5MP; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	
 Ш.5357	DAHUA HAC-HFW1500TLM-IL-A - 3.6mm 5MP Smart Dual Light HDCVI Fixed-focal Bullet Camera Max 25 fps@5MP ;Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	
 Ш.5358	DAHUA HAC-PT1500A-IL-A - 2.8mm 5MP Smart Dual Light HDCVI Fixed-focal PT Camera Max. 25 fps@5MP; Smart Dual Light; Smart Area Lighting; Pan & Tilt; 40 m illumination distance; Super Adapt; Built-in Mic; 2.8mm fixed lens; IP66, 12 VDC.	

HDCVI 5MP Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.5359	DAHUA HAC-HDW1509TLQ-LED - 3.6mm 5MP Full-color HDCVI Quick-to-install Eyeball Camera Max 25 fps@5MP (16:9 video output); 120dB true WDR, 3D NR; 24/7 color image; 20 m illumination distance; CVI/CVBS/AHD/TVI switchable; IP67, 12 V DC;	
 Ш.5360	HAC-HFW1509C-LED - 2.8mm with Audio 5MP Full-color HDCVI Bullet Camera Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; 24/7 color imaging; 20 m illumination distance 2.8 mm fixed lens; IP67, 12V DC	
 Ш.5361	HAC-HFW1509C-A-LED - 2.8mm with Audio 5MP Full-color HDCVI Bullet Camera Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; 24/7 color imaging; 20 m illumination distance; Built-in mic; 2.8 mm fixed lens; IP67, 12V DC	
 Ш. 5362	DAHUA HAC-HFW1509T-A-LED - 3.6mm with Audio 5MP Full-color HDCVI Bullet Camera Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; 24/7 color imaging; 20 m illumination distance ;Built-in mic (-A); 3.6 mm lens; IP67, 12 V DC	
 Ш. 5363	DAHUA HAC-HFW1509TLM-A-LED - 3.6mm with Audio 5MP Full-color HDCVI Bullet Camera Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; 24/7 color imaging; 40 m illumination distance; Built-in mic (-A); 3.6 mm fixed lens; IP67, 12 V DC;	

HDCVI 8MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.8360	DAHUA HAC-HDW1801T-IL-A - 2.8mm 4K Smart Dual Light HDCVI Fixed-focal Eyeball Camera Max. 15 fps@4K; 120 dB true WDR, 3D NR; Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 2.8 mm fixed lens; IP67, 12 VDC;	
 Ш.8361	DAHUA HAC-HFW1801TLM-IL-A - 3.6mm 4K Smart Dual Light HDCVI Fixed-focal Bullet Camera Max. 15 fps@4K; 120 dB true WDR, 3D NR; Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	

HDCVI 8MP Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.8362	DAHUA HAC-HDW1809T-A-LED - 2.8mm 4K Full-Color HDCVI Eyeball Camera Max. 15 fps@4K; 120 dB true WDR, 3D NR; 24/7 color imaging 40 m illumination distance; Super Adapt; Built-in MIC(-A); IP67, 12 VDC.	
 Ш.8363	DAHUA HAC-HFW1809TLM-A-LED - 3.6mm 4K Full-Color HDCVI Bullet Camera Max. 15 fps@4K; 120 dB true WDR, 3D NR; 24/7 color imaging; 40 m illumination distance; Super Adapt; Built-in MIC(-A); 3.6 mm fixed lens; IP67, 12 VDC;	

HDCVI 8MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш. 8364	DAHUA HDW1800TL-A - 2.8mm 4K Real-time HDCVI IR Eyeball Camera Max. 4K resolution, real-time video transmission, Built-in mic (-A), Max. IR length 30mCVI/CVBS/AHD/TVI switchable, Smart IR, IP67, 12V±30%DC	
 Ш. 8365	DAHUA HAC-HFW1800TL-A - 3.6mm 4K Real-time HDCVI IR Bullet Camera ax. 4K resolution, real-time video transmission; CVI/CVBS/AHD/TVI switchable Built-in mic (-A); 2.8 Fixed lens; Max. IR length 80m, Smart IR; IP67, 12V±30%DC	
 Ш. 8366	DAHUA HAC-HFW1801TL-A - 3.6mm 4K Real-time HDCVI IR Bullet Camera 4K resolution, real-time video transmission; CVI/CVBS/AHD/TVI switchable Built-in mic (-A); 2.8 Fixed lens; Max. IR length 80m, Smart IR; IP67, 12V±30%DC	
 Ш. 8367	DAHUA HAC-HFW1800TH-I8 – 3.6mm 4K Real-time HDCVI IR Bullet Camera Max. 4K resolution, real-time video transmission; CVI/CVBS/AHD/TVI switchable; Max. IR length 80m, Smart IR; IP67, 12V±30%DC	
 Ш. 8368	DAHUA HAC-HFW1801TH-I8 - 3.6mm 4K Starlight HDCVI Fixed IR Bullet Camera Max. 15 fps@4K; 120 dB true WDR, 3D NR; Smart IR Illumination; 80 m illumination distance; Super Adapt; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC.	
 Ш. 8369	DAHUA HFW1801R-Z-IRE6 with Audio 2.7-13.5mm 4K 8MP HDCVI IR Bullet Camera 120dB true WDR, 3D NR Max. 4K resolution, CVI/CVBS/AHD/TVI switchable, Auto focus, Motorized lens, Max. IR length 60m, smart IR, IP67, 12V ±30% DC	
 Ш. 8370	DAHUA HAC-HFW2802TU-A – 3.6mm 4K Starlight HDCVI Fixed-focal Bullet Camera Max. 15 fps@4K; Starlight, 120 dB true WDR, 3D NR; Smart IR Illumination; 80 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	

HDCVI Pan/Tilt/Zoom Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.9001	DAHUA SD49225DB-HC 2MP 25x Starlight IR HDCVI PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS; Powerful 25x optical zoom; Starlight technology; 120 dB true WDR, 3D NR; Max. 25/30 fps@1080p, 25/30/50/60 fps@720p; IR distance up to 100 m; IP66;	
 Ш.9002	DAHUA SD49225-HC -LA 2MP 25x Starlight IR PTZ HDCVI Camera 1/2.8" 2Megapixel STARVIS™ CMOS; Powerful 25x optical zoom; Starlight technology; Max. 25/30fps@1080P, 25/30/50/60fps@720P, 120dB true WDR, 3D DNR, IR distance up to 100m, IP66	
 Ш.9003	DAHUA NKB1000-E Network Keyboard	

Specialized Cameras

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.0010	DAHUA IPC-HFW7442H-ZFR 4MP IR Bullet WizMind Network Camera Max outputs 4MP (2688 × 1520) @50 fps/60 fps; 12V DC power output; 4MP, 1/1.8" CMOS image sensor, low illuminance, high image definition;	
 Ш.0011	DAHUA TPC-BF5421-T Thermal Network Hybrid Bullet Camera Vanadium oxide uncooled focal plane detector; Built-in white light and speaker; Features temperature measurement; Micro SD memory, IP67, PoE, ePoE	
 Ш.0012	DAHUA JQ-D70Z Thermometric Blackbody	
 Ш.0013	DAHUA ITC413-PW4D Series Dahua Access ANPR Camera High-performance CMOS image sensor and processor that supports continuously extracting metadata 24/7; Easily adapts to scenarios through its motorized vari-focal lens; Adopts intelligent deep learning algorithms and supports recognition of unlicensed vehicles and the type, brand and color of vehicles;	

Digital Video Recorder Up to 2MP

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.201	DAHUA XVR1B04-I 4 Channel Penta-brid 1080N/720p Cooper 1U WizSense H.265+/H.265 dual-stream video compression; Supports Full channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 5 channels IP camera inputs, each channel up to 2MP; Max 20 Mbps incoming bandwidth	
 Ш.202	DAHUA XVR1B08-I 8 Channel Penta-brid 1080N/720p Cooper 1U WizSense H.265+/H.265 dual-stream video compression; Supports Full channel AI-Coding Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 10 channels IP camera inputs, each channel up to 6MP; Max 40 Mbps incoming bandwidth;	
 Ш.203	DAHUA XVR1B16-I 16 Channel Penta-brid 1080N/720p Compact 1U WizSense H.265+/H.265 dual-stream video compression; Supports Full-channel AI-Coding Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 18 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps Incoming Bandwidth;	

Digital Video Recorder Up to 6MP

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.601	DAHUA XVR5104HS-I3 4 Channel Penta-brid 5M-N/1080p Compact 1U WizSense Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 6 channels IP camera inputs, each channel up to 6MP; Up to 1 channel video stream Perimeter Protection; Up to 4 channels video stream SMD Plus; Up to 1 channel video stream human face recognition;	
 Ш.602	DAHUA XVR5104HS-I3(1TB) 4CH Penta-brid 5MP Value/1080P Compact 1U 1SSD 1TB WizSense Comes with an internal 1TB SSD, and can record videos for about 22 days. 4-channel SMD Plus for analog channels which allows the device to trigger accurate alarms for humans and vehicles. 1-channel face recognition for analog channels which supports face comparison.	
 Ш.603	DAHUA XVR5108HS-I3 8 Channel Penta-brid 5M-N/1080p Compact 1U WizSense H.265+/H.265 dual-stream video compression; Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 12 channels IP camera inputs, each channel up to 6MP; Up to 1 channel video stream Perimeter Protection; Up to 8 channels video stream SMD Plus;	
 Ш.604	DAHUA XVR5108HS-I3(1TB) 8CH Penta-brid 5MP Value/1080P Compact 1U 1SSD 1TB WizSense Comes with an internal 1TB SSD, and can record videos for about 11 days. 8-channel SMD Plus for analog channels which allows the device to trigger accurate alarms for humans and vehicles. 4-channel perimeter protection for analog channels which supports tripwire and intrusion detection powered by AI.	
 Ш.605	DAHUA XVR5116HS-I3 – WizSense 16 Channel Penta-brid 5M-N/1080P Compact Digital Video Recorder H.265+/H.265 dual-stream video compression; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth; Perimeter Protection and SMD Plus; IoT & POS functionalities	

 Ш.606	DAHUA XVR5232AN-I3 32 Channels Penta-brid WizSense Digital Video Recorder H.265+/H.265 dual-stream video compression. · Supports 16-channel AI-Coding. · Supports HDCVI/AHD/TVI/CVBS/IP video inputs. · Max 32 channels IP camera inputs, each channel up to 6MP; IoT & POS functionalities.	
Digital Video Recorder Up to 8MP		
МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.801	DAHUA XVR5104HS-4KL-I3 4 Channel Penta-brid 5MP Compact 1U WizSense Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 8 channels IP camera inputs, each channel up to 8MP; Up to 1 channel video stream Perimeter Protection; Up to 4 channels video stream SMD Plus; Up to 1 channel video stream human face recognition	
 Ш.802	DAHUA XVR5108HS-4KL-I3 - WizSense 8 Channel Penta-brid 4K-N/5MP Compact 1U Digital Video Recorder H.265+/H.265 dual-stream video compression; Supports DCVI/AHD/TVI/CVBS/IP video inputs; Max 16 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; Perimeter Protection and SMD Plus;	
 Ш.803	DAHUA XVR7108H-4K-I3 8 Channels Penta-brid 4K Mini WizSense Digital Video Recorder H.265+/H.265 dual-stream video compression. Supports 8-channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 16 channels IP camera inputs, each channel up to 8MP; IoT & POS functionalities.	
 Ш.804	DAHUA XVR5116H-4KL-I3 16 Channels Penta-brid 4K-N/5MP Mini 1U WizSense H.265+/H.265 dual-stream video compression; · Supports Full-channel AI-Coding; Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; IoT & POS functionalities;	
 Ш.805	DAHUA XVR5216A-4KL-I3 16 Channels Penta-brid 4K-N/5MP 1U WizSense H.265+/H.265 dual-stream video compression; Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; IoT & POS functionalities;	
 Ш.806	DAHUA XVR7216A-4KL-X – Pro Series 16 Channel Penta-brid 4K 1U Digital Video Recorder H.265+/H.265 dual-stream video compression; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Supports 16/32 channels of IPC access, each channel up to 8MP input; Max 64/128Mbps Incoming Bandwidth;	
 Ш.807	DAHUA XVR7216AN-4K-I3 16 Channels Penta-brid 4K 1U 2HDDs WizSense Digital Video Recorder H.265+/H.265 dual-stream video compression; Supports 16-channel AI-Coding Supports HDCVI/AHD/TVI/CVBS/IP ; Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; Up to 16 channels video stream SMD plus; IoT & POS functionalities	
 Ш.808	DAHUA XVR5232AN-4KL-I3 32 Channels Penta-brid 4K-N/5MP WizSense Digital Video Recorder. H.265+/H.265 dual-stream video compression.; Supports 32-channel AI-Coding.; Supports HDCVI/AHD/TVI/CVBS/IP video inputs.; Max 32 channels IP camera inputs, each channel up to 8MP; IoT & POS functionalities.	

IPC Smart-Dual Light 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.2210	DAHUA IPC-HFW1239TL1-A-IL 2MP Entry Smart Dual Light Fixed-focal Bullet Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Built-in IR LED and warm light, the max. IR illumination distance is 30 m and warm light distance is 30 m; Supports human detection; 12 VDC/PoE power supply;	
 Ш.2211	Dahua IPC-HDW139V-A-IL 2MP Entry Smart Dual Light Fixed-focal Eyeball Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 2 MP (1920×1080)@25/30 fps; Built-in IR LED and warm light, the max. IR illumination distance is 30m and warm light distance is 30 m;	

IPC Full-Color 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.2212	DAHUA IPC-HFW5249T-ASE-NI – Pro AI Series 2MP Pro AI Full-color Fixed-focal Bullet Network Camera 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition; Outputs max. 2MP (1920×1080) @ 30 fps; H.265 codec, SMART H.264+/H.265; 12V DC/PoE power support; ePoE for remote transmission · IP67 protection	

IPC 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.2213	DAHUA IPC-HDW1230T1-S5 2MP Entry IR Fixed-Focal Eyeball Network Camera 2-MP 1/2.8" CMOS image sensor, low illuminance, high image definition; Outputs max. 2 MP (1920 × 1080) @25/30 fps; H.265 codec, high compression rate, ultra-low bit rate; IR illuminator, and the max. illumination distance is 30m.	
 Ш.2208	DAHUA IPC-HFW1230S1-S5 2MP Entry IR Fixed-Focal Bullet Network Camera 2-MP 1/2.8" CMOS image sensor, low illuminance, high image definition; Outputs max. 2 MP (1920 × 1080) @25/30 fps; H.265 codec, high compression rate, ultra-low bit rate; IR illuminator, and the max. illumination distance is 30 m;	
 Ш.2214	DAHUA IPC-HDBW1230E 2MP IR Mini-Dome Network Camera 1/2.7" 2Megapixel progressive CMOS; H.265 & H.264 dual-stream encoding; 25/30fps@1080P(1920x1080); Day/Night(ICR), 3DNR, AWB, AGC, BLC; Multiple network monitoring; 2.8mm fixed lens; Max IR LEDs length 30m; IP67, IK10, PoE	
 Ш.2215	DAHUA SD22204UE-GN – Lite Series 2MP 4x Starlight PT Network Camera 1/2.8" STARVIS™ CMOS; Powerful 4x optical zoom; Day/Night(ICR), Ultra DNR; Max. 25/30fps@1080P; Max 100°/s pan speed · IVS Support PoE; IP66, IK10	
 Ш.2216	DAHUA IPC-HFW2231TP-ZS-S2 – Lite Series 2MP Lite IR Vari-focal Bullet Network Camera 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition; Outputs 2MP; H.265 codec, ultra-low bit rate; Built-in IR LED, max IR distance: 60m; Supports max. 256 GB Micro SD card; 12V DC/PoE ; IP67 ,IK10	

 Ш.2217	DAHUA IPC-HFW4231T-ASE with Audio 3.6mm 2MP WDR IR Mini Bullet Network Camera 1/2.8" 2Megapixel progressive scan STARVISTM CMOS; H. 265&H.264 triple-stream encoding; 50/60fps@1080P(1920×1080), 60 Hz ;WDR(120dB), Day/Night (ICR), 3DNR, AWB, AGC, BLC;LEDs Length 60m; Micro SD Memory,IP67,IK10, PoE	
 Ш.2218	DAHUA IPC-HFW5242E-ZE-MF – WizMind 2MP IR Vari-focal Bullet WizMind Network Camera 1/1.8" 2Megapixel progressive scan CMOS; ROI, SMART H.264+/H.265+, flexible coding; 50/60 fps@1080P (1920 × 1080); Day/Night (ICR), 3D DNR, AWB, BLC ; 2.7 mm–12.0 mm motorized; IR LEDs Length 50 m; Micro SD memory, IP67, IK10	

IPC 4MP FULL-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.4210	DAHUA IPC-HFW2439S-SA-LED-S2 4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" CMOS image sensor, low illuminance, high image definition; Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP (2688 × 1520)@20 fps; Built-in warm lights, max. illumination distance: 30 m;	

IPC 4MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.4211	DAHUA IPC-HFW1431T-ZS-S4 4MP Entry IR Vari-focal Bullet Network Camera 4MP, 1/3" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, max. IR distance: 50 m; 12V DC/PoE power supply;	

IPC 5MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.5213	DAHUA IPC-HDBW2541E-S 5MP IR Fixed-focal Dome WizSense Network Camera 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 5 MP (2960 × 1668) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps; 12 VDC/PoE power supply, easy for installation.	
 Ш.5214	DAHUA IPC-HFW1530S-S6 5MP Entry IR Fixed-focal Bullet Network Camera 5MP 1/2.7" CMOS image sensor, low luminance, and high definition image; · Outputs max. 5MP @20 fps and supports 2688 × 1520 @25/30 fpS; Built-in IR LED, and the max. illumination distance is 30 m.	
 Ш.5215	DAHUA IPC-HFW2531S-S-S2 – Lite Series 3.6mm 5MP Lite IR Fixed-focal Bullet Network Camera 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition · Outputs 2688×1520@25/30 fps, and supports max. 5MP (2592×1944);Built-in IR LED, IR distance: 30 m; 12V DC/PoE power support ; IP67 protection grade	
 Ш.5216	DAHUA IPC-HFW2541E-S 5MP IR Fixed-focal Bullet WizSense Network Camera 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 5 MP (2592 × 1944) @20 fps, and supports 4 MP (2688 × 1520) @25/30 fps;Abnormality detection: Motion detection, video tampering, scene changing, audio detection, IP conflict, illegal access, and voltage detection	

IPC 8MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.8210	DAHUA IPC-HFW2849S-S-IL 8MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps; Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m	
 Ш.8211	DAHUA IPC-HDW2849TM-S-IL 8MP Smart Dual Light Fixed-focal Eyeball WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps; Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m;	
 Ш.8212	DAHUA IPC-HFW2849T-AS-IL 8MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP @20 fps, and supports 2688×1520 @25/30 fps; Built-in warm light and IR LED, IR light distance is 60 m and max. warm light is 50 m;	

IPC 6MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.6210	DAHUA IPC-HDW1639T-A-IL 6MP Smart Dual Light Fixed-focal Eyeball Network Camera 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 6 MP@20 fps, and supports 2688 × 1520@25/30fps;Built-in Multi-core Light, the max. IR distance is 30 m and the max. warm light distance is 30 m;	
 Ш.6211	DAHUA IPC-HFW1639TC-A-IL 6MP Smart Dual Light Fixed-focal Bullet Network Camera 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 6MP @20 fps, and supports 2688 × 1520@25/30 fps; H.265 codec, Built-in Multi-core Light, the max. IR distance is 30 m and the max. warm light distance is 30 m;	

IPC 8MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.8213	DAHUA IPC-HDW2831T-AS-S2 2.8mm 8MP Lite IR Fixed-focal Eyeball Network Camera 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition; H.265 codec;; Built-in IR LED, max IR distance: 30 m; ROI, SMART H.264+/H.265+, flexible coding; 256 GB Micro SD card, built-in MIC; 12V DC/PoE ; IP67;	
 Ш.8214	DAHUA HDBW2841R-ZAS 8MP IR Vari-focal Dome WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, and the max. illumination distance is 40 m; ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments;	
 Ш.8215	DAHUA IPC-HDBW2841E-S 8MP IR Fixed-focal Dome WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps; Built-in IR LED, and the max. illumination distance is 30 m;	
 Ш.8216	DAHUA IPC-HFW2831S-S-S2 8MP Lite IR Fixed-focal Bullet Network Camera 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, max IR distance: 30 m; 12V DC/PoE power support; IP67 protection	
 Ш.8217	IPC-HFW2831T-AS-S2 3.6mm 8MP Lite IR Fixed-focal Bullet Network Camera 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, max IR distance: 80 m; Intelligent detection: Intrusion, tripwire; Alarm: 1 in, 1 out;	
 Ш.8218	DAHUA IPC-HFW2841T-AS 8MP IR Fixed-focal Bullet WizSense Network Camera Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520@25/30 fps. Built-in IR LED, and the max. illumination distance is 80 m; Alarm: 1 in, 1 out ; audio: 1 in, 1 out ; Supports max. 256 G Micro SD card; built in MIC.	
 Ш.8219	DAHUA IPC-HFW2841T-ZAS 8MP IR Vari-focal Bullet WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Built-in IR LED, and the max. illumination distance is 60 m. Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.	
 Ш.8220	DAHUA IPC-HFW2831TP-ZS – Lite Series 8MP WDR IR Bullet Network Camera 1/1.8" 8Megapixel progressive CMOS; H.265 & H.264 dual-stream encoding 25/30fps@8MP(3840×2160); WDR(120dB), Micro SD card slot, up to 128GB; 3.7~11mm motorized lens; Max IR LEDs Length 60m; IP67, IK10(optional), PoE	
 Ш.8221	DAHUA IPC-HFW3849T1-AS-PV-S3 8MP Smart Dual Illumination Active Deterrence Bullet Camera 8MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160)@25/30 fps.; Built-in warm light and IR LED; the max. IR illumination distance is 30 m and warm light distance is 30 m; Alarm: 1 in, 1 out; audio: 1 in, 1 out;	

IPC Pan/Tilt/Zoom Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.1111	DAHUA SD49225GB-HNR 2MP 25x Starlight IR Network PTZ Camera 1/2.8" STARVIS™ CMOS; 25x optical zoom; Starlight technology; Max.25/30fps@2M; IR distance up to 100 m; Perimeter protection; Face detection;Quick Pick; SMD 4.0; IP66.	
 Ш.1112	DAHUA SD4A425DB-HNY 4MP 25x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ CMOS; 25x optical zoom; Starlight technology; Max. 25/30fps@4MP; IR distance up to 100m; Auto-tracking 1.0; Perimeter protection; Face detection; SMD 3.0; IP66.	
 Ш.1113	DAHUA SDT4E425-4F-GB-A-PV1 X-Spans 4MP+4MP 25x TiOC WizSense Network PTZ Camera 1/2.8" 4Megapixel F1.0 CMOS; Detail: 1/2.8"4Megapixel STARVIS™ CMOS; 25x optical zoom; Max. 25/30fps@4M; IR distance up to 100 m; Auto tracking 3.0; Smart tracking; Perimeter protection; Active deterrence; Smart dual light +;	
 Ш.1114	DAHUA SD49825GB-HNR 8MP 25x Starlight IR Network PTZ Camera 1/2.8" 8Megapixel STARVIS™ CMOS; 25x optical zoom; Starlight technology; Max. 25/30fps@8M; IR distance up to 100 m; Perimeter protection; Face detection; Quick Pick; SMD 4.0; IP66;	
 Ш.1115	DAHUA SDT4E425-8P-GB-APV1 8+4MP 25x TiOC Network Panoramic PTZ Camera Overview channel: Outputs 180° wide angle splicing image; Detail channel: 1/2.8"4Megapixel STARVIS™ CMOS; 25x optical zoom; Max. 25/30 fps@8M; IR distance up to 100 m; Auto tracking 3.0; Smart tracking; Perimeter protection; Active deterrence; Smart dual light +;	
 Ш.1116	DAHUA IPC-PFW8802-A180 4x2MP Multi-Sensor Panoramic IR Bullet Network Camera Four 1/1.9" 2Megapixel progressive scan CMOS; H.265/H.264 triple-stream encoding; Support 180-degree panoramic view; Day/Night(ICR), 3DNR, AWB, AGC, BLC, WDR; Smart detection; Max. IR length 30m; Micro SD memory, IP67, IK10,PoE+	

IPC 2MP/4MP Wi-Fi Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.7010	DAHUA H4A 4MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera One Camera for 360° View; Human Detection; Day&Night; Auto Tracking; Two-way Talk; One-click Privacy Mode;	
 Ш.7011	DAHUA H4C 4MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera One Camera for 360° View; Human Detection; Day&Night; Auto Tracking; Two-way Talk; One-click Privacy Mode;	
 Ш.7014	DAHUA IPC-HDW1430DT-STW 4MP IR Fixed-focal WiFi Eyeball Network Camera Outputs max. 4MP@20 fps, and max.supports 3MP@25 fps/30 fps; Built-in IR LED, and the max. illumination distance is 30 m; Built-in dual-antenna 2.4G Wi-Fi that covers a range of up to 120m;	
 Ш.7015	DAHUA IPC-HDBW1430DE-SW 4MP IR Fixed-focal Wi-Fi Dome Network Camera 4-MP 1/3" CMOS image sensor, low luminance, and high definition image.H.265 codec, high compression rate, ultra-low bit rate. · Built-in IR LEDSupports max. 256 G Micro SD card. · 12 VDC · IP67, IK10 protection	
 Ш.7115	DAHUA SD1A203T-GN-W – IR-15m 2MP 3x Starlight IR PTZ Wi-Fi Network Camera 1/2.8" 2Megapixel STARVIS™ CMOS , Powerful 3x optical zoom, Starlight, WDR, Max. 5/30fps@1080P, IVS, Support Wi-Fi,, IP66	

IPC 4MP Wi-Fi Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.7016	DAHUA T4A 4MP Fixed-focal Wi-Fi Full-Color Turret Network Camera AI Human Detection; Full-color; Built-in Mic; IP67 Protection; Advanced H.265 compression technology;	
 Ш.7017	DAHUA F4C-LED 4MP Fixed-focal Wi-Fi Full-Color Bullet Network Camera AI Human Detection; Full-color; Built-in Mic; IP67 Protection; Advanced H.265 compression technology;	

IPC 4MP/5MP Wi-Fi Smart Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.7018	DAHUA F4C-PV 4MP Fixed-focal Wi-Fi Smart Dual-Light Bullet Network Camera AI Human Detection; Smart Dual Light; Sound and Light Alarm; Two-way Talk; IP67 Protection; Advanced H.265 compression technology; Built-in warm light and IR LED, and the max. illumination distance is 30 m.	
 Ш.7019	DAHUA P5AE-PV 5MP Wireless Smart Dual-Light Network PT Camera Smart Dual Light; One Camera for 360° View; Sound and Light Alarm; AI Human Detection; AI Vehicle Detection; Two-way Talk; Auto Tracking; IP66 Protection;	
 Ш.7020	DAHUA P5B-PV 5MP Outdoor Fixed-focal Wi-Fi Pan & Tilt Network Camera 360° monitoring without blind spots; Sound and Light Alarm Provides instant alarms to deter intruders; AI Human Detection; AI Vehicle Detection; Auto Tracking; Fast pairing with Bluetooth; Seamless integration of speed and anti-interference; Two-way audio;	
 Ш.7120	DAHUA T4A-PV 4MP Clear images with sharp details; Sound and Light Alarm; Advanced H.265 compression technology; AI Human Detection; Two-way Talk; DMSS App Easy to use; Smart Dual Light; IP67 Protection; SD Card Low-cost storage;	
 Ш.7121	DAHUA P5D-5F-PV 5+5MP Outdoor Wi-Fi Dual-Lens Pan & Tilt Camera Dual Channel Smart Detection; AI Human Detection; Dual 3K; Dual-lens, Double Vision; Adjustable Dual-lens Angles; Auto Tracking; Preset Patrol; IP66 Protection; Smart Dual Light; Sound and Light Alarm; Bluetooth Pairing; Wi-Fi 6; H.265;	

Network Video Recorder

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.1000	DAHUA NVR2108-S3 8 Channel Smart 1U 1HDD Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264 decoding format; Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding; AI by camera: perimeter protection, and SMD Plus; Connected to the third-party network cameras · Security baseline 2.1;	
 Ш.1001	DAHUA NVR2116-S3 16 Channel Smart 1U 1HDD Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264 decoding format; Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding ; AI by camera: perimeter protection, and SMD Plus; Connected to the third-party network cameras; Security baseline 2.1;	
 Ш.1002	NVR4104HS-4KS3 4 Channel Compact 1U 1HDD Network Video Recorder New 4.0 user interface, Security baseline Max. decoding capability; 8 × 1080p@30 fps. Supports adaptive decoding; Supports mainstream cameras of ONVIF and RTSP protocols; P2P remote surveillance, video play on mobile device; VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K;	
 Ш.1003	DAHUA NVR4104HS-EI 4CH Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 80 Mbps; Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	
 Ш.1004	DAHUA NVR4104HS-P-4KS3 4CH Compact 1U 4PoE 1HDD Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats. Max. decoding capability: 8 × 1080p@30 fps or 4 × 4 MP@30 fps; Max. 80/80/60 Mbps incoming/recording/outgoing bandwidth; Supports IP cameras with a resolution up to 12 MP; AI by Camera supports face detection and recognition, perimeter; protection, SMD Plus, people counting.	
 Ш.1005	DAHUA NVR4108HS-4KS3 8CH Compact 1U 1HDD Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 8 × 1080p@30 fps; Max. 80/80/60 Mbps incoming/recording/outgoing bandwidth; Supports IP cameras with a resolution up to 12 MP; AI by Recorder supports 4-channel SMD Plus;	
 Ш.1006	DAHUA NVR4108HS-8P-EI 8CH Compact 1U 8PoE 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled); Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection;	
 Ш.1007	DAHUA NVR4108HS-8P-4KS3 8 Channel Compact 1HDD 1U 8PoE Network Video Recorder H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch; Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding; Supports mainstream cameras of ONVIF and RTSP protocols; P2P remote surveillance,	

 Ш.1008	DAHUA NVR4116HS-EI 16CH Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled); AI by NVR; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	
 Ш.1009	DAHUA NVR4216-4KS2/L 16 Channel 1U 2HDDs Network Video Recorder New 4.0 user interface, Security baseline 2.1; H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch; Supports mainstream cameras of ONVIF and RTSP protocols; P2P remote surveillance, video play on mobile device	
 Ш.1010	DAHUA NVR4116-8P-4KS2/L 16 Channel Smart 1U 1HDD 8PoE Network Video Recorder New 4.0 user interface, Security baseline 2.1 · H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch; Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding; Supports mainstream cameras of ONVIF and RTSP protocols; P2P remote surveillance, video play on mobile device;	
 Ш.1011	DAHUA NVR4216-4KS2/L 16 Channel 1U 2HDDs Network Video Recorder New 4.0 user interface, Security baseline 2.1; H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch; Supports mainstream cameras of ONVIF and RTSP protocols; P2P remote surveillance, video play on mobile device	
 Ш.1012	DAHUA NVR4216-16P-EI 16CH 1U 16PoE 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by NVR; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	
 Ш.1013	DAHUA NVR4232-EI 32CH 1U 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled); Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by Camera: Face detection and recognition, perimeter protection;	
 Ш.1014	DAHUA NVR5232-EI 32 Channels 1U 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps; Max. 384 Mbps incoming/recording/outgoing bandwidth; Support AcuPick with Max. 16-Channel; Support N+M cluster;	
 Ш.1015	DAHUA NVR5464-EI 64 Channels 1.5U 4HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps; Max. 384 Mbps incoming/recording/outgoing bandwidth; Support AcuPick with Max. 16-Channel;	

