

Time Attendance / Access Control

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
 Ш.300	M-SC405 ID card Capacity 30,000; Transaction Capacity 80,000/100,000(For 64M); Communication TCP/IP, RS485*; Host Access Control Interface for 3rd party electric lock, door sensor, exit button, alarm, doorbell; Auxiliary Interface 1ea for linkage function; Wiegand Signal Output & Input; SRB Standard Functions ID Card, Automatic Status Switch, Self-Service Query, DST, 9 Digit User ID, Scheduled Bell, Anti-passback; Optional Functions IC Card, Print Function; Display TFT LCD Color Screen; Power Supply DC 12V; Operating Temperature 0°C ~ 45°C; Operating Humidity 20% ~ 80%; Dimension (L×W×H) 143x96x42mm;	

Access Control – Standalone

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
 Ш.301	ACM-210H Tuya-WIFI Access Control (IC) , IP68 Outdoor Touch Screen DoorBell; Access Control; Card type: IC; User Capacity:1000 Operating Voltage:DC 12V; Waterproof: IP68; Dimensions:L148 x W43.5 x H22 (mm)	
 Ш.302	M-HF3-BT Tuya Smart Bluetooth Access Control APP name:TuyaSmart Power: DC12V-18V; Unlock by: Fingerprint, ID card, Password, APP; Support Fingerprint/ID card/Password maximum 255 User by APP	
 Ш.303	M-CH1 Tuya WiFi Waterproof Touch Keypad Access Control Power: DC12V; Unlock by: ID card, Password, APP; Support 1000 Users; Waterproof IP66; With dingdong call button;	
 Ш.304	X6 ZKTEC fingerprint Technical Specifications Reliable, durable & highly accurate optical sensor Up to 500 Card Capacity .Up to 500 Fingerprint Capacity Less than 1 second user recognition Reads Fingerprint and/or Password and/or card Password Capacity up to 8 groups Integrated 125kHz RFID proximity reader Small Rugged elegant design. Audio indications for acceptance and rejection of valid/invalid transactions 3rd Party Electric Lock, Alarm, Door Sensor, Exit Button and doorbell Standard ID Card while MF card as optional feature	

Standalone & Network Contactless Readers and Encoders

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
 Ш.305	APM-253F Keypad RFID Access Place of origin: Guangdong, China; Brand name: ACM; Wiegand: WG26 / 34 Input and output port; Product Name: Touch Screen PIN Keypad RFID Access Control	
 Ш.306	ACM-223 Keypad RFID Access Control Communication port: TCP/IP, RS485, USB Host; Communication: WEIGAND; Fingerprint Capacity: 1000; Card Capacity: 4,000 Cards; Log Capacity: 10,000 Transactions; RFID Card: EM(standard)/MF(optional); Authentication: Finger/PIN/Card	
 Ш.307	M-K202 nezavisen citac na 125KHz bezkontaktni karticki so tastatura za kontrola na pristap, nadvoresna ili vnatresna upotreba, modovi na rabota: PIN, karticka i PIN+karticka	
 Ш.308	RT381E-ID Status Indicator; RFID Smart card swiping area; Door bell button; Photoresistor can trigger disassembly alarm; DIP Switch;	
 Ш.310	RT381E-IC Status Indicator; RFID Smart card swiping area; Door bell button; Photoresistor can trigger disassembly alarm; DIP Switch;	
 Ш.311	M-140 METAL KEY PAD Nezavisen (so vgraden kontroler) citac na bezkontaktni karticki vo metalno kukiste so svetlecka tastatura za kontrola na pristap so PIN, karticka i PIN+karticka, vnatresna upotreba, 2.000 korisnici, 1 vlez, 2 relejni izlezi, porta za povrzuvawe na slave citac	
 Ш.312	GCW-108C-EMW Outdoor Waterproof access control	
 Ш.313	AG32B-EMW -Outdoor , Outdoor Waterproof Access controller	

Access Control – Standalone

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА БЕЗ ДДВ
 Ш.314	DAHUA ASA3213GL-MW Face Recognition Time & Attendance 4.3-inch LCD touch screen; resolution 480 × 272; With 2MP wide-angle dual lens, white LED illuminator, IR light; Support face, card and password attendance; Support 500 users, 500 face images, 500 cards, 150,000 records and work without network; Face-camera distance: 0.3 m–1.5 m; Face verification accuracy 99.5%;	
 Ш.315	DAHUA ASI2212H-DW Access Standalone PC + ABS, suitable for indoor and outdoor use; 2.4" LCD screen with a resolution of 240 × 320; IP65 rated (silicone sealant is needed, see Quick Start Guide; Option to switch between reader and controller mode for added convenience; Card/remote/password/ fingerprint unlock and unlock through their combinations;	
 Ш.316	DAHUA ASI2212H-W - Mifare Access Standalone PC + ABS, suitable for indoor and outdoor use; 2.4" LCD screen with a resolution of 240 × 320; IP65 rated (silicone sealant is needed, see Quick Start Guide; Option to switch between reader and controller mode for added convenience; Card/remote/password/ fingerprint unlock and unlock through their combinations;	
 Ш.317	DAHUA ASI1201E-D Water-proof RFID Standalone Support 30,000 valid cards & 60,000 records; Support multiple cards (default IC card) Support card, password and combination; TCP/IP to PC; Wiegand or RS-485 interface to reader; Door time out alarm, intrusion alarm, duress alarm and tamper alarm;	
 Ш.318	DAHUA ASI1201E – Mifare Water-proof RFID Standalone Support 30,000 valid cards & 60,000 records; Support multiple cards (default IC card) Support card, password and combination; TCP/IP to PC; Wiegand or RS-485 interface to reader; Door time out alarm, intrusion alarm, duress alarm and tamper alarm;	
 Ш.319	DAHUA ASI1201A-D Standalone Reader Touch keyboard and LCD display; Support 30,000 valid cards & 150,000 records; Support multiple cards (default IC card) (“-D” means ID EM card); Support card, password and combination ; TCP/IP to PC; Wiegand or RS-485 interface to reader; Door time out alarm, intrusion alarm, duress alarm and tamper alarm; Anti-passback;	

Access Control – Slave

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.320	DAHUA ASA1222G-D Time & Attendance Terminal Supports Mifare card/ID card reading distance 1 cm-3 cm, card swiping response time; Fingerprint verification response time ≤0.5 s, fingerprint recognition times ≤1.5 s; Operating temperature: 0°C to +55°C , operating humidity: ≤93%; Supports three attendance modes: fixed, manual/auto and forced;	

Access Control – Slave

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.321	DAHUA ASR1101A-D RFID Reader Support RS485, Wiegand34 protocol(Wiegand 26 optional); 13.56MHz(Mifare) · 125KHz(EM-ID); Red and Green LEDs; Sensitive touch keypad with blue backlight; Watch dog function ensure device free from halting; Beep Buzzer and LED indicator; Surface mounted installation	
 Ш.322	ASR1102A-D(V2) Fingerprint RFID Reader RS-485 protocol; Default IC (Mifare) card ("-D" means ID EM card); Support card, fingerprint; Up to 3000 fingerprints capacity; Blue backlight; Watch dog function ensure device free from halting; Beep and indicator; Surface mounted installation;	
 Ш.323	DAHUA ASR1200E-D Water-proof RFID Reader Wiegand34(26 optional) bits RS-485 protocol; 13.56MHz(Mifare); 125KHz(EM-ID); Water-proof design; Red, blue and green indicator LEDs; Surface mounted installation	
 Ш.324	DAHUA ASR1201D-D Slim Water-proof RFID Reader Support RS485, Wiegand34 protocol(Wiegand 26 optional); 13.56MHz(Mifare) 125KHz(EM-ID); Red and Blue LEDs; Watch dog function ensure device free from halting; Water-proof(Outdoor use); Surface/Flush mounted installation	

Controllers

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.325	DAHUA ASC2104B-T Four Door Slave Access Control Module Support 20,000 valid cards & 30,000 records; Support multiple cards; Support card, password, fingerprint and combination; Only work with ASC2204-H with CAN bus;Wiegand or RS-485 interface to readers; Door time out alarm, intrusion alarm, duress alarm and tamper alarm;	
 Ш.326	M-C3-200 Two-door Two-way Controller , Card:30,000 , Event Buffer:100,000; Reader Port:2ea(26/34bits wiegand, 8bits burst for PIN) ,Communication: RS485	
 Ш.327	M-C3-400 Four-door One-way Controller , Card:30,000 , Event Buffer:100,000; Reader Port:4ea(26/34bits wiegand, 8bits burst for PIN) , Communication: RS485	
 Ш.328	Four Door Two Way Access Controller DAHUA ASC1204C-D	
 Ш.329	Four Door Master Access Controller DAHUA ASC2204C-H	
 Ш.330	DEE1010B - Access Control Extension Module Decent appearance; Easy connection; Access control function extension	

Accessories - ID Card, Tag and Bracelet 125KHz

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
Ш.331 	IDC01 ID Card 125KHz Clamshell Thick	
Ш.332 	IDC03 ID Card 125KHz Clamshell Thick MANGO	
Ш.333 	IDC04 ID Card 125KHz Printable Thin	
Ш.300z 	IDC07 ID Card 125KHz Blue Empty	
Ш.300 	IDC02 ID TAG 125KHz EM Proximity TAG . Color Optional: Blue , Black , Grey	
Ш.300 	IDC10 ID Tag 125KHz Blue Empty	
Ш.300 	IDC09 ID 125KHz EM Silikon Wristband <i>waterproof</i>	


IC-Mifare Cards, Tags and Bracelets (13.56MHz)

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
 Ш.300	ICC05 IC Card Mifare 13.56MHz	
 Ш.300	IC-C50 Dahua IC card MIFARE Card (13.56MHz) High data transmission speed: 106 k bit/sData integrity protection: 16 bit CRC, odd-even check, encoding and counting by bit.Anti-conflicData transmission and	
 Ш.300	MF11CS50 Dahua IC card MIFARE Card (13.56MHz)	
 Ш.300	ICC08 IC Card Mifare 13.56MHz Empty	
 Ш.300	ICC06 IC Tag Mifare 13.56MHz	
 Ш.300	ICC09 IC Mifare 1K Silicon Wristband waterproff	
 Ш.300	ICC09/1 IC Mifare silicon Wristband waterproof	

Energy Saver, Tasteri, Touch buttons, Bravi

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
 Ш.300	Energy sawing ID Switch 125KHz with Flush Read Format: ID Switc 125KHz , Voltage: AC180V~240V ; Max load: 6600w ; Power delay time: 15s ; Working Environment: -10°C ~ +70°C ; Working Humidity: ≤95%	
 Ш.300	Energy sawing IC Mifare Switch 13.56MHz Read Format: 13.56MHz (Mifare card); Voltage: AC180V~240V ; Max load: 6600w ; Power delay time: 15s ; Working Environment: -10°C ~ +70°C ; Working Humidity: ≤95%	
	Push Button NT86 No touch Door Release Exit Sensor	

	Touch Button T50	
--	------------------	---

	Touch Button T86	
	DEB02 Wired Door Exit Push Button HOT & NEW!	
	Taster Z30 - Metalen Door exit push trigger switch for access control; Switching output: NO / COM contacts; Standard Structure: aluminum panels, metal button	
	EP-BM30 Door Retractor	
	CL132N Long type Electric Strike safety door lock Current:400mA; Voltage:12/24VDC; Certification:CE/MA; Lock; Status: NO/NC/COM/+/-; Lock Size: Magnet(LxWx H):110x25x31mm; Suitable For:Wooden Door,Glass Door,Metal Door,Glass Door; Induction Distance:8mm	
	ACM-Y180M EM lock (180kgs/300lbs) (so drzaci) Lock size: 170x40x21mm Holding force: 180KG; Working voltage: 12V DC Working current: 400mA	
	Single Door EM Lock (180kg/300lbs)	
	EM Lock , LED Indicator, Timer Function (280kg/600lbs)	
	M-203 EM Lock , BOLT LOCK Zinc alloy body case,Full metal mechanical structure Bolt:SUS304 solid stainless steel bolt , Voltage: DC12V-DC24V , Induction distance:8mm , Force holding:1000 Kg , 2 lines time delay:0,3,6,9 sec	
	L Bracket for 180 and 280kgs EM Lock	
	<u>Z Bracket for 180 and 280kgs EM Lock</u>	