

	<b>Touch Button T86</b>	
	<b>DEB02</b> Wired Door Exit Push Button HOT & NEW!	
	<b>Taster Z30 - Metalen</b> Door exit push trigger switch for access control; Switching output: NO / COM contacts; Standard Structure: aluminum panels, metal button	
	<b>EP-BM30 Door Retractor</b>	
	<b>CL132N Long type Electric Strike safety door lock</b> Current:400mA; Voltage:12/24VDC; Certification:CE/MA; Lock; Status: NO/NC/COM/+/-; Lock Size: Magnet( LxWx H):110x25x31mm; Suitable For:Wooden Door,Glass Door,Metal Door,Glass Door; Induction Distance:8mm	
	<b>ACM-Y180M EM lock (180kgs/300lbs) (so drzaci)</b> Lock size: 170x40x21mm Holding force: 180KG; Working voltage: 12V DC Working current: 400mA	
	<b>Single Door EM Lock (180kg/300lbs)</b>	
	<b>EM Lock , LED Indicator, Timer Function (280kg/600lbs)</b>	
	<b>M-203 EM Lock , BOLT LOCK</b> Zinc alloy body case,Full metal mechanical structure Bolt:SUS304 solid stainless steel bolt , Voltage: DC12V-DC24V , Induction distance:8mm , Force holding:1000 Kg , 2 lines time delay:0,3,6,9 sec	
	<b>L Bracket for 180 and 280kgs EM Lock</b>	
	<b>Z Bracket for 180 and 280kgs EM Lock</b>	