

Accessories - ID Card, Tag and Bracelet 125KHz

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
Ш.331 	IDC01 ID Card 125KHz Clamshell Thick	
Ш.332 	IDC03 ID Card 125KHz Clamshell Thick MANGO	
Ш.333 	IDC04 ID Card 125KHz Printable Thin	
Ш.300z 	IDC07 ID Card 125KHz Blue Empty	
Ш.300 	IDC02 ID TAG 125KHz EM Proximity TAG . Color Optional: Blue , Black , Grey	
Ш.300 	IDC10 ID Tag 125KHz Blue Empty	
Ш.300 	IDC09 ID 125KHz EM Silikon Wristband <i>waterproof</i>	

IC-Mifare Cards, Tags and Bracelets (13.56MHz)

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
 Ш.300	ICC05 IC Card Mifare 13.56MHz	
 Ш.300	IC-C50 Dahua IC card MIFARE Card (13.56MHz) High data transmission speed: 106 k bit/sData integrity protection: 16 bit CRC, odd-even check, encoding and counting by bit.Anti-conflicData transmission and	
 Ш.300	MF11CS50 Dahua IC card MIFARE Card (13.56MHz)	
 Ш.300	ICC08 IC Card Mifare 13.56MHz Empty	
 Ш.300	ICC06 IC Tag Mifare 13.56MHz	
 Ш.300	ICC09 IC Mifare 1K Silicon Wristband waterproff	
 Ш.300	ICC09/1 IC Mifare silicon Wristband waterproof	

Energy Saver, Tasteri, Touch buttons, Bravi

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
 Ш.300	Energy sawing ID Switch 125KHz with Flush Read Format: ID Switc 125KHz , Voltage: AC180V~240V ; Max load: 6600w ; Power delay time: 15s ; Working Environment: -10°C ~ +70°C ; Working Humidity: ≤95%	
 Ш.300	Energy sawing IC Mifare Switch 13.56MHz Read Format: 13.56MHz (Mifare card); Voltage: AC180V~240V ; Max load: 6600w ; Power delay time: 15s ; Working Environment: -10°C ~ +70°C ; Working Humidity: ≤95%	
	Push Button NT86 No touch Door Release Exit Sensor	