

Time Attendance / Access Control

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА СО ДДВ
 Ш.300	M-SC405 ID card Capacity 30,000; Transaction Capacity 80,000/100,000(For 64M); Communication TCP/IP, RS485*; Host Access Control Interface for 3rd party electric lock, door sensor, exit button, alarm, doorbell; Auxiliary Interface 1ea for linkage function; Wiegand Signal Output & Input; SRB Standard Functions ID Card, Automatic Status Switch, Self-Service Query, DST, 9 Digit User ID, Scheduled Bell, Anti-passback; Optional Functions IC Card, Print Function; Display TFT LCD Color Screen; Power Supply DC 12V; Operating Temperature 0°C ~ 45°C; Operating Humidity 20% ~ 80%; Dimension (LxWxH) 143x96x42mm;	
 Ш.314	DAHUA ASA3213GL-MW Face Recognition Time & Attendance 4.3-inch LCD touch screen; resolution 480 × 272; With 2MP wide-angle dual lens, white LED illuminator, IR light; Support face, card and password attendance; Support 500 users, 500 face images, 500 cards, 150,000 records and work without network; Face-camera distance: 0.3 m-1.5 m; Face verification accuracy 99.5%;	
 Ш.320	DAHUA ASA1222G-D Time & Attendance Terminal Supports Mifare card/ID card reading distance 1 cm-3 cm, card swiping response time; Fingerprint verification response time ≤0.5 s, fingerprint recognition time≤1.5 s; Operating temperature: 0°C to +55°C , operating humidity: ≤93%; Supports three attendance modes: fixed, manual/auto and forced;	