



 **omen** *Servis*

БЕЗБЕДНОСНИ СИСТЕМИ

- ✓ Видео надзор
- ✓ Контрола на пристап
- ✓ Видеофонија
- ✓ Домофонија
- ✓ Интернет мрежа
- ✓ Алармни системи
- ✓ Автоматика на врати

Продажба-Монтажа-Сервис



FAAC
Simply automatic.

alhua
TECHNOLOGY

AJAX
WIRELESS ALARMS

078 841 602 

www.omenservis.com   @omenservis.stip

Цените се со пресметан ДДВ 5% и 18% .

Гаранција на производите е 12 – 24 месеци.

Омен Сервис го задржува правото на промена на цените без претходна најава.

HDCVI 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.2340	DAHUA HAC-T1A21-U – 2.8mm 2MP HDCVI IR Eyeball Camera Max. 30 fps@1080p; Smart IR Illumination; 25 m illumination distance; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable;	
 Ш.2341	DAHUA HAC-T2A21-U – 2.8mm 2MP IR HDCVI Fixed-focal Eyeball Camera Max. 30 fps@1080p; Smart IR Illumination; 30 m illumination distance; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	
 Ш.2342	DAHUA HAC-HDW1200T-Z-A 2MP HDCVI IR Eyeball Camera Max 30fps@1080P; HD and SD output switchable; Built-in mic; 2.7-12mm motorized lens; Max. IR length 60m, Smart IR; IP67, DC12V	
 Ш.2343	DAHUA HUM1220G-B - 2.8mm 2MP HDCVI Bullet Camera Max 30fps@1080P, 2.8mm fixed lens, DC12V; HD and SD output switchable;	
 Ш.2344	DAHUA HAC-HUM3200A 2MP IR HDCVI Fixed-focal Cube Camera Max 30 fps@1080p; 10 m illumination distance (940nm IR No IR Exposure); Super Adapt; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable; 12 VDC;	
 Ш.2345	DAHUA HAC-B1A21-U – 3.6mm 2MP IR HDCVI Fixed-focal Bullet Camera Max. 30 fps@1080p; Smart IR Illumination; 30 m illumination distance; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	
 Ш.2348	DAHUA HAC-HFW1231TM-I8-A – 3.6mm 2MP Starlight HDCVI IR Bullet Camera Max 30 fps@1080p; Starlight, 130 dB true WDR, 3D NR; 3.6 mm fixed lens; Super Adapt; Built-in mic; Max. IR length 80 m, Smart IR; IP67, DC 12 V;	
 Ш.2349	DAHUA LC1220T-TH - IoT Series - 2.8mm 2MP HDCVI Temperature & Humidity Camera Max 30fps@1080P, 2.8mm fixed lens, Max. IR length 20m, Detection range: -40°C~60°C, 10-95% RH, Smart IR, IP67, DC12V	

HDCVI 2MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.2350	DAHUA HAC-HDW1200TLM-IL-A 2MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic; 2.8 mm fixed lens; IP67, 12 VDC;	
 Ш.2351	DAHUA HAC-HFW1200CM-IL-A 2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic; 2.8 mm fixed lens; IP67, 12 VDC;	
 Ш.2352	DAHUA HAC-HDW1200CLQ-IL-A – 2.8mm 2MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic; 2.8 mm fixed lens ; CVI/CVBS/AHD/TVI switchable; 12 VDC.	
 Ш.2353	DAHUA HAC-HFW1200CL-IL-A – 2.8mm 2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera Max. 30 fps@1080p; 3D NR; Smart Dual Light; 20 m illumination distance; Super Adapt; Built-in mic; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; 12 VDC.	
 Ш.2373	DAHUA HAC-HFW1200RL-IL-T – 2.8mm 2MP Smart Dual Light HDCVI Two-way Talk Fixed-focal Bullet Camera Max. 30 fps@1080p; Two-way Talk; Smart Dual Light; Smart Light+; 3D NR; 30 m illumination distance; 2.8 mm fixed lens ; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	
 Ш.2354	DAHUA HAC-HFW1200TLM-IL-A - 2.8mm 2MP Smart Dual Light HDCVI Fixed-focal Bullet Camera Max. 30 fps@1080p; 3D NR; Smart Dual Light; 40m illumination distance; Super Adapt; Built-in mic; 2.8mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12VDC	

HDCVI 2MP Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.2355	DAHUA HAC-HDW1209TLQ-A-LED - 2.8mm 2MP Full-color HDCVI Quick-to-install Eyeball Camera 24/7 color imaging; 20 m illumination distance; Max. 30 fps@1080p; Built-in mic; CVI/CVBS/AHD/TVI switchable; IP67, 12V±30% DC;	



HDCVI 5MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.5351	DAHUA HAC-T1A51-U – 2.8mm 5MP IR HDCVI Fixed-focal Eyeball Camera Max 25 fps@5MP (16:9 video output); Smart IR Illumination; 25 m illumination distance; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable;	
 Ш.5352	DAHUA HAC-B1A51-U – 2.8mm 5MP IR HDCVI Fixed-focal Bullet Camera Max 25 fps@5MP (16:9 video output); Smart IR Illumination; 30 m illumination distance; 2.8 mm fixed lens; CVI/CVBS/AHD/TVI switchable. · IP67, 12 VDC.	
 Ш.5255	DAHUA HAC-HDW1500TRQ-A – 2.8mm 5MP Starlight HDCVI Quick-to-install IR Eyeball Camera Max 25 fps@5MP (16:9 video output); Built-in mic (-A); CVI/CVBS/AHD/TVI switchable; 2.8 mm fixed lens; Max. IR length 25M; Smart IR; IP50, DC12V;	
 Ш.5353	DAHUA HAC-EW2501 5MP HDCVI IR-Fisheye Camera 1/2.8" 5Megapixel progressive scan CMOS; Panoramic fisheye lens; Max. 20fps@5MP; Built-in Mic; 120dbtrue WDR, Starlight, 2D&3D NR; Max. IR length 10m, Smart IR; DC12V	
 Ш.5354	UTC Controller PFM820 Support different formats (HDCVI/AHD/HDTVI/CVBS) switch, which ito satisfy the requirements of different storage device environments for clients;	

HDCVI 5MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.5355	DAHUA HAC-HDW1500CLQ-IL-A 2.8mm 5MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera Max 25 fps@5MP (16:9 video output); Smart Dual Light; 20m illumination distance; Super Adapt; Built-in MIC; CVI/CVBS/AHD/TVI switchable; IP67,12 VDC	
 Ш.5356	DAHUA HAC-HFW1500RL-IL-T – 2.8mm 5MP Smart Dual Light HDCVI Two-way Talk Fixed-focal Bullet Camera Max. 25 fps@5MP; Two-way Talk; Smart Dual Light; Smart Light+; 3D NR; 30 m illumination distance; 2.8 mm fixed lens ; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	
 Ш.5357	DAHUA HAC-HFW 1 500TLM-IL-A – 3.6mm 5MP Smart Dual Light HDCVI Fixed-focal Bullet Camera Max 25 fps@5MP ;Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	
 Ш.5388	DAHUA HAC-HFW1509TLM-IL-A – 3.6mm 5MP Smart Dual Light Bullet Camera Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	
 Ш.5389	DAHUA HAC-HFW1500TH-IL-A – 3.6mm 5MP Smart Dual Light HDCVI Fixed-focal Bullet Camera Max. 25 fps@5MP (16:9 video output); Starlight, 3D NR; Smart Dual Light; 80 m illumination distance; Built-in Mic; 3.6 mm fixed lens; IP67, 12 VDC;	
 Ш.5358	DAHUA HAC-PT1500A-IL-A – 2.8mm 5MP Smart Dual Light HDCVI Fixed-focal PT Camera Max. 25 fps@5MP; Smart Dual Light; Smart Area Lighting; Pan & Tilt; 40 m illumination distance; Super Adapt; Built-in Mic; 2.8mm fixed lens; IP66, 12 VDC.	

5MP WizColor HDCVI Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.5390	DAHUA HAC-HDW1549X-IL-A-PRO - 2.8mm 5MP WizColor HDCVI Fixed-focal Eyeball Camera Max. 25 fps@5MP (16:9 video output); AI-ISP; Distortion Correction; Smart Dual Light; Smart Light+; 50 m illumination distance; Super Adapt,130 dB true WDR, 3D NR; Built-in Dual Mic; 3.6 mm fixed lens; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	
 Ш.5390	DAHUA HAC-HFW1549X-IL-A-PRO 5MP WizColor HDCVI Fixed-focal Bullet Camera Max. 25 fps@5MP (16:9 video output); AI-ISP; Distortion Correction; Smart Dual Light; Smart Light+; 50 m illumination distance; Super Adapt,130 dB true WDR, 3D NR; Built-in Dual Mic; 2.8 mm fixed lens ; CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC;	

HDCVI 5MP Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.5359	DAHUA HAC-HDW1509TLQ-LED - 3.6mm 5MP Full-color HDCVI Quick-to-install Eyeball Camera Max 25 fps@5MP (16:9 video output); 120dB true WDR, 3D NR;24/7 color image;20 m illumination distance; CVI/CVBS/AHD/TVI switchable;IP67, 12 V DC;	
 Ш.5360	HAC-HFW1509C-LED – 2.8mm with Audio 5MP Full-color HDCVI Bullet Camera Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; 24/7 color imaging; 20 m illumination distance 2.8 mm fixed lens; IP67, 12V DC	
 Ш.5361	HAC-HFW1509C-A-LED – 2.8mm with Audio 5MP Full-color HDCVI Bullet Camera Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; 24/7 color imaging; 20 m illumination distance; Built-in mic; 2.8 mm fixed lens; IP67, 12V DC	
 Ш. 5362	DAHUA HAC-HFW1509T-A-LED – 3.6mm with Audio 5MP Full-color HDCVI Bullet Camera Max 25 fps@5MP (16:9 video output); 120 dB true WDR, 3D NR; 24/7 color imaging; 20 m illumination distance ;Built-in mic (-A); 3.6 mm lens; IP67, 12 V DC	
 Ш. 5363	HAC-HFW1509TLM-A-LED – 3.6mm 5MP Full-color HDCVI Fixed-focal Bullet Camera Max 25 fps@5MP (16:9 video output) 120 dB true WDR, 3D NR; 24/7 color imaging; Smart Light+; Smart Area Lighting; Built-in Mic; 40 m illumination distance; CVI/CVBS/AHD/TVI switchable; 3.6 mm fixed; IP67, 12 VDC;	

HDCVI 8MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.8360	DAHUA HAC-HDW1801T-IL-A – 2.8mm 4K Smart Dual Light HDCVI Fixed-focal Eyeball Camera Max. 15 fps@4K; 120 dB true WDR, 3D NR; Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 2.8 mm fixed lens; IP67, 12 VDC;	
 Ш.8361	DAHUA HAC-HFW1801TLM-IL-A – 3.6mm 4K Smart Dual Light HDCVI Fixed-focal Bullet Camera Max. 15 fps@4K; 120 dB true WDR, 3D NR; Smart Dual Light; 40 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	

HDCVI 8MP Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.8362	DAHUA HAC-HDW1809T-A-LED – 2.8mm 4K Full-Color HDCVI Eyeball Camera Max. 15 fps@4K; 120 dB true WDR, 3D NR; 24/7 color imaging 40 m illumination distance; Super Adapt; Built-in MIC(-A); IP67, 12 VDC.	

HDCVI 8MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш. 8364	DAHUA HDW1800TL-A - 2.8mm 4K Real-time HDCVI IR Eyeball Camera Max. 4K resolution, real-time video transmission, Built-in mic (-A), Max. IR length 30mCVI/CVBS/AHD/TVI switchable, Smart IR, IP67, 12V±30%DC	
 Ш. 8365	DAHUA HAC-HFW1800TL-A - 3.6mm 4K Real-time HDCVI IR Bullet Camera ax. 4K resolution, real-time video transmission; CVI/CVBS/AHD/TVI switchable Built-in mic (-A); 2.8 Fixed lens; Max. IR length 80m, Smart IR; IP67, 12V±30%DC	
 Ш. 8366	DAHUA HAC-HFW1801TL-A - 3.6mm 4K Real-time HDCVI IR Bullet Camera 4K resolution, real-time video transmission; CVI/CVBS/AHD/TVI switchable Built-in mic (-A); 2.8 Fixed lens; Max. IR length 80m, Smart IR; IP67, 12V±30%DC	
 Ш. 8367	DAHUA HAC-HFW1800TH-I8 – 3.6mm 4K Real-time HDCVI IR Bullet Camera Max. 4K resolution, real-time video transmission; CVI/CVBS/AHD/TVI switchable; Max. IR length 80m, Smart IR; IP67, 12V±30%DC	
 Ш. 8368	DAHUA HAC-HFW1801TH-I8 - 3.6mm 4K Starlight HDCVI Fixed IR Bullet Camera Max. 15 fps@4K; 120 dB true WDR, 3D NR; Smart IR Illumination; 80 m illumination distance; Super Adapt;CVI/CVBS/AHD/TVI switchable; IP67, 12 VDC.	
 Ш. 8369	DAHUA HFW1801R-Z-IRE6 with Audio 2.7-13.5mm 4K 8MP HDCVI IR Bullet Camera 120dB true WDR, 3D NR Max. 4K resolution, CVI/CVBS/AHD/TVI switchable,Auto focus, Motorized lens, Max. IR length 60m, smart IR, IP67, 12V ±30% DC	
 Ш. 8370	DAHUA HAC-HFW2802TU-A – 3.6mm 4K Starlight HDCVI Fixed-focal Bullet Camera Max. 15 fps@4K; Starlight, 120 dB true WDR, 3D NR; Smart IR Illumination; 80 m illumination distance; Super Adapt; Built-in MIC; 3.6 mm fixed lens; IP67, 12 VDC;	

HDCVI Pan/Tilt/Zoom Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.9002	DAHUA SD49225-HC -LA 2MP 25x Starlight IR PTZ HDCVI Camera 1/2.8" 2Megapixel STARVIS™ CMOS, Powerful 25x optical zoom, Starlight technology, Max. 25/30fps@1080P, 25/30/50/60fps@720P, 120dB true WDR, 3D DNR, IR distance up to 100m, IP66	
 Ш.9003	DAHUA NKB1000-E Network Keyboard	

Specialized Cameras

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.0010	DAHUA IPC-HFW7442H-ZFR 4MP IR Bullet WizMind Network Camera Max outputs 4MP (2688 × 1520) @50 fps/60 fps; 12V DC power output; 4MP, 1/1.8" CMOS image sensor, low illuminance, high image definition;	
 Ш.0011	DAHUA TPC-BF5421-T Thermal Network Hybrid Bullet Camera Vanadium oxide uncooled focal plane detector; Built-in white light and speaker; Features temperature measurement; Micro SD memory, IP67, PoE, ePoE	
 Ш.0012	DAHUA JQ-D70Z Thermometric Blackbody	
 Ш.0013	DAHUA ITC413-PW4D Series Dahua Access ANPR Camera High-performance CMOS image sensor and processor that supports continuously extracting metadata 24/7; Easily adapts to scenarios through its motorized vari-focal lens; Adopts intelligent deep learning algorithms and supports recognition of unlicensed vehicles and the type, brand and color of vehicles;	

Digital Video Recorder Up to 2MP

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.201	DAHUA XVR1B04-I 4 Channel Penta-brid 1080N/720p Cooper 1U WizSense H.265+/H.265 dual-stream video compression; Supports Full channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 5 channels IP camera inputs, each channel up to 2MP; Max 20 Mbps incoming bandwidth	
 Ш.202	DAHUA XVR1B08-I 8 Channel Penta-brid 1080N/720p Cooper 1U WizSense H.265+/H.265 dual-stream video compression; Supports Full channel AI-Coding Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 10 channels IP camera inputs, each channel up to 6MP; Max 40 Mbps incoming bandwidth;	
 Ш.203	DAHUA XVR1B16-I 16 Channel Penta-brid 1080N/720p Compact 1U WizSense H.265+/H.265 dual-stream video compression; Supports Full-channel AI-Coding Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 18 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps Incoming Bandwidth;	

Digital Video Recorder Up to 6MP


МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.601	DAHUA XVR5104HS-I3 4 Channel Penta-brid 5M-N/1080p Compact 1U WizSense Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 6 channels IP camera inputs, each channel up to 6MP; Up to 1 channel video stream Perimeter Protection; Up to 4 channels video stream SMD Plus; Up to 1 channel video stream human face recognition;	
 Ш.602	DAHUA XVR5104HS-I3(1TB) 4CH Penta-brid 5MP Value/1080P Compact 1U 1SSD 1TB WizSense Comes with an internal 1TB SSD, and can record videos for about 22 days. 4-channel SMD Plus for analog channels which allows the device to trigger accurate alarms for humans and vehicles. 1-channel face recognition for analog channels which supports face comparison.	
 Ш.603	DAHUA XVR5108HS-I3 8 Channel Penta-brid 5M-N/1080p Compact 1U WizSense H.265+/H.265 dual-stream video compression; Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 12 channels IP camera inputs, each channel up to 6MP; Up to 1 channel video stream Perimeter Protection; Up to 8 channels video stream SMD Plus;	
 Ш.604	DAHUA XVR5108HS-I3(1TB) 8CH Penta-brid 5MP Value/1080P Compact 1U 1SSD 1TB WizSense Comes with an internal 1TB SSD, and can record videos for about 11 days. 8-channel SMD Plus for analog channels which allows the device to trigger accurate alarms for humans and vehicles. 4-channel perimeter protection for analog channels which supports tripwire and intrusion detection powered by AI.	
 Ш.605	DAHUA XVR5116HS-I3 – WizSense 16 Channel Penta-brid 5M-N/1080P Compact Digital Video Recorder H.265+/H.265 dual-stream video compression; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth; Perimeter Protection and SMD Plus; IoT & POS functionalities	

 Ш.606	DAHUA XVR5232AN-I3 32 Channels Penta-brid WizSense Digital Video Recorder H.265+/H.265 dual-stream video compression. · Supports 16-channel AI-Coding. · Supports HDCVI/AHD/TVI/CVBS/IP video inputs. · Max 32 channels IP camera inputs, each channel up to 6MP; IoT & POS functionalities.	
Digital Video Recorder Up to 8MP		
МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.801	DAHUA XVR5104HS-4KL-I3 4 Channel Penta-brid 5MP Compact 1U WizSense Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 8 channels IP camera inputs, each channel up to 8MP; Up to 1 channel video stream Perimeter Protection; Up to 4 channels video stream SMD Plus; Up to 1 channel video stream human face recognition	
 Ш.802	DAHUA XVR5108HS-4KL-I3 - WizSense 8 Channel Penta-brid 4K-N/5MP Compact 1U Digital Video Recorder H.265+/H.265 dual-stream video compression; Supports DCVI/AHD/TVI/CVBS/IP video inputs; Max 16 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; Perimeter Protection and SMD Plus;	
 Ш.803	DAHUA XVR7108H-4K-I3 8 Channels Penta-brid 4K Mini WizSense Digital Video Recorder H.265+/H.265 dual-stream video compression. Supports 8-channel AI-Coding. Supports HDCVI/AHD/TVI/CVBS/IP video inputs. Max 16 channels IP camera inputs, each channel up to 8MP; IoT & POS functionalities.	
 Ш.804	DAHUA XVR5116H-4KL-I3 16 Channels Penta-brid 4K-N/5MP Mini 1U WizSense H.265+/H.265 dual-stream video compression; · Supports Full-channel AI-Coding; Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; IoT & POS functionalities;	
 Ш.805	DAHUA XVR5216A-4KL-I3 16 Channels Penta-brid 4K-N/5MP 1U WizSense H.265+/H.265 dual-stream video compression; Supports Full-channel AI-Coding; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; IoT & POS functionalities;	
 Ш.806	DAHUA XVR7216A-4KL-X – Pro Series 16 Channel Penta-brid 4K 1U Digital Video Recorder H.265+/H.265 dual-stream video compression; Supports HDCVI/AHD/TVI/CVBS/IP video inputs; Supports 16/32 channels of IPC access, each channel up to 8MP input; Max 64/128Mbps Incoming Bandwidth;	
 Ш.807	DAHUA XVR7216AN-4K-I3 16 Channels Penta-brid 4K 1U 2HDDs WizSense Digital Video Recorder H.265+/H.265 dual-stream video compression; Supports 16-channel AI-Coding Supports HDCVI/AHD/TVI/CVBS/IP ; Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth; Up to 16 channels video stream SMD plus; IoT & POS functionalities	
 Ш.808	DAHUA XVR5232AN-4KL-I3 32 Channels Penta-brid 4K-N/5MP WizSense Digital Video Recorder. H.265+/H.265 dual-stream video compression.; Supports 32-channel AI-Coding.; Supports HDCVI/AHD/TVI/CVBS/IP video inputs.; Max 32 channels IP camera inputs, each channel up to 8MP; IoT & POS functionalities.	

Hard Disk Drive

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.0100	DAHUA HDD 1TB Seagate 1000G/5900RPM/64M/ SATA 6Gb/s/ Dahua LOGO ST1000VX013 SEAGATE , SURVEILLANCE 24x7 Operation	
 Ш.0101	DAHUA HDD 2TB Seagate 2000G/5900RPM/64M/ SATA 6Gb/s/ Dahua LOGO ST2000VX017 SEAGATE , SURVEILLANCE 24x7 Operation	
 Ш.0102	DAHUA HDD 4TB Seagate 4000G/7200RMP/64M/ SATA 6Gb/s/ Dahua LOGO , ST4000VX016 SEAGATE SURVEILLANCE , 24x7 Operation	
 Ш.0103	DAHUA HDD 6TB Seagate 6000G/7200RMP/64M/ SATA 6Gb/s/ Dahua LOGO , ST6000VX009 SEAGATE SURVEILLANCE , 24x7 Operation	
 Ш.0104	DAHUA HDD 8TB Seagate 8000G/7200RMP/64M/ SATA 6Gb/s/ Dahua LOGO , ST8000VX010 SEAGATE SURVEILLANCE , 24x7 Operation	

Memory Card & USB Flash Drive

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.0105	DHI-TF-C100/64GB microSD Memory Card	
 Ш.0106	DHI-TF-C100/128GB microSD Memory Card	
 Ш.0107	DHI-TF-C100/256GB microSD Memory Card	
 Ш.0108	DHI-USB-P629-32-64GB USB Flash Drive	
 Ш.0109	DHI-USB-P629-32-128GB USB Flash Drive	
 Ш.0110	DHI-USB-P629-32-256GB USB Flash Drive	

IPC Smart-Dual Light 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.2210	DAHUA IPC-HFW1239TL1-A-IL 2MP Entry Smart Dual Light Fixed-focal Bullet Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Built-in IR LED and warm light, the max. IR illumination distance is 30 m and warm light distance is 30 m; Supports human detection; 12 VDC/PoE power supply;	
 Ш.2410	DAHUA IPC-T1E29-A-IL 2MP ECO Smart Dual Light Fixed-focal Eyeball Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 2 MP (1920 × 1080)@30 fps; Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 1 m; Built in Mic; PoE; IP67 protection;	
 Ш.2411	DAHUA IPC-HDBW139E1-A-IL 2MP Entry Smart Dual Light Fixed-focal Dome Network Camera 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image.; Outputs max. 2 MP (1920 × 1080)@25/30 fps; Built-in IR LED and warm light, and the max. IR distance is 30 m, the max. warm light distance is 30 m; Built in Mic; 12 VDC/PoE power supply, easy for installation; IP67 and IK08 protection; Supports human detection;	
 Ш.2412	DAHUA IPC-PT1239H-PV 2MP Smart Dual Light Active Deterrence Network PT Camera 1/2.8" 2Megapixel CMOS; Max. 25/30 fps@2MP; H.265 Encoding; Human/Vehicle Detection; Perimeter Protection; Active Deterrence; Smart Dual Light; Two-way Talk; Easy App Controls;	

IPC 2MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.2213	DAHUA IPC-T1E20-A 2MP ECO IR Fixed-focal Eyeball Network Camera 2MP 1/3.2" CMOS image sensor, low luminance, and high definition image; Outputs max. 2 MP (1920 × 1080)@30 fps; Built-in IR LED, and the max. illumination distance is 30 m; Built in Mic; 12 VDC power supply; IP67 protection;	
 Ш.2313	DAHUA IPC-B1E20-A 2MP ECO IR Fixed-focal Bullet Network Camera 2MP 1/3.2" CMOS image sensor, low luminance, and high definition image; Outputs max. 2 MP (1920 × 1080)@30 fps; Built-in IR LED, and the max. illumination distance is 30; Built in Mic; 12 VDC power supply; IP67 protection;	
 Ш.2214	DAHUA IPC-HDBW1230E 2MP IR Mini-Dome Network Camera 1/2.7" 2Megapixel progressive CMOS; H.265 & H.264 dual-stream encoding; 25/30fps@1080P(1920x1080); Day/Night(ICR), 3DNR, AWB, AGC, BLC; Multiple network monitoring: 2.8mm fixed lens; Max IR LEDs length 30m; IP67, IK10, PoE	
 Ш.2215	DAHUA SD22204UE-GN – Lite Series 2MP 4x Starlight PT Network Camera 1/2.8" STARVIS™ CMOS; Powerful 4x optical zoom; Day/Night(ICR), Ultra DNR; Max. 25/30fps@1080P; Max 100°/s pan speed · IVS Support PoE; IP66, IK10	
 Ш.2217	DAHUA IPC-HFW4231T-ASE with Audio 3.6mm 2MP WDR IR Mini Bullet Network Camera 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS; H. 265&H.264 triple-stream encoding; 50/60fps@1080P(1920x1080), 60 Hz ;WDR(120dB), Day/Night (ICR), 3DNR, AWB, AGC, BLC;LEDs Length 60m; Micro SD Memory,IP67,IK10, PoE	

IPC 2MP WizColor Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.2217	DAHUA IPC-HFW2249TL-S-PRO 2MP WizColor Fixed-focal Bullet WizSense Network Camera 2-MP 1/2.9" CMOS image sensor, low luminance, and high definition image; Outputs max. 2 MP (1920 × 1080)@25/30 fps; H.265 codec, high compression rate, ultra-low bit rate; Built-in warm light, and the max. illumination distance is 50 m; Built-in warm light, and the max. illumination distance is 50 m;	

IPC 4MP Full-Color/Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.4217	DAHUA IPC-HFW2439S-SA-LED-S2 – 3.6mm 4MP Lite Full-color Fixed-focal Bullet Network Camera 4MP, 1/3" CMOS image sensor, low illuminance, high image definition; Outputs MP (2560 × 1440) @ 25/30 fps, M x. supports 4MP (2688 × 1520)@20 fps; Built-in warm lights, max. illumination distance: 30 m;	
 Ш.4218	DAHUA IPC-B1E49-A-IL 4MP ECO Smart Dual Light Fixed-focal Bullet Network Camera 4-MP 1/3" CMOS image sensor, low luminance, and high definition image; Outputs max. 4 MP (2560 × 1440)@30 f s; Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 15 m; Built in Mic; PoE power supply, easy for installation; IP67 protection; Supports human detection;	
 Ш.4219	DAHUA IPC-HDBW139E1-A-IL 4MP Entry Smart Dual Light Fixed-focal Dome Network Camera 4-MP 1/3" CMOS image sensor, low luminance, and high definition image; Outputs Max. 4 MP (2560 × 1440)@25/30 fps; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED and warm light, and the max. IR distance is 30 m, the max. warm light distance is 30 m; Built in Mic; 12 VDC/PoE power supply, IP67 and IK08 protection;	
 Ш.42	DAHUA IPC-PT1439 -PV – 2.8mm 4MP Smart Dual Light ctive Deterrence Network PT Camera 1/2.8" 4Megapixel CMOS; Max. 25/30 fps@4MP; H.265 Encoding; Human/Vehicle Detection; Perimeter Protection; Active Deterrence; Smart Dual Light; Two-way talk; Easy App Controls;	

IPC 4 MP WIZCOLOR CAMERA

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.4410	DAHUA SD2C400NA-B-PV-PRO 4MP WizColor WizSense Network PT Camera 1/1.8" 4Megapixel STARVIS™ CMOS; WizColor technology; Max. 25/30 fps@4MP; H.265 encoding; SMD3.0; Perimeter protection; Two-way Talk; Aut Tracking(Lite); Preset Patrol; IP66 protection;	
 Ш.4470	DAHUA IPC-HDBW2449E-S-IL 4MP Smart Dual Light Fixed-focal Dome WizSense Network Camera 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image; Outputs max. 4 MP (2688 × 1520) @20 fps, and supports 2560 × 1440@25/30 fps; Built-in IR LED and warm light, the max. IR illumination distance is 30 m and the max. warm light distance is 30 m.12 VDC/PoE power supply, easy for installation; IP67, IK10 protection; SMD Plus;	
 Ш.4471	DAHUA IPC-HDW2449T-S-PRO 4MP WizColor Fixed-focal Eyeball WizSense Network Camera 4-MP 1/1.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 4 MP (2688 × 1520) @20 fps, and supports 2560×1440 (2560 × 1440) @25/30 fps; Built-in warm light, and the max. illumination distance is 30m; Supports max. 256 G MicroSD card; built in Mic; 12 VDC/PoE power supply, easy for installation; IP67 protection; SMD Plus;	
 Ш.4411	DAHUA IPC-HFW2449TL-S-PRO – 2.8mm 4MP WizColor Fixed-focal Bullet WizSense Network Camera 4-MP 1/1.8" CMOS image sensor, low luminance, and high definition image; Built-in warm light, and the max. illumination distance is 50 m; Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection; Supports max. 256 G Micro SD card; built in Mic;	

IPC 4MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.4211	DAHUA IPC-HFW1431T-ZS-S4 4MP Entry IR Vari-focal Bullet Network Camera 4MP, 1/3" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate Built-in IR LED, max. IR distance: 50 m; 12V DC/PoE power supply;	
 Ш.4212	DAHUA IPC-T1E40-A – 2.8mm 4MP ECO IR Fixed-focal Eyeball Network Camera MP 1/3" CMOS image sensor, low luminance, and high definition image.; Outputs max. 4 MP (2560 × 1440)@30 fps; H.265 codec, high compression rate, ultra-low bit rate; and the max. illumination distance is 30 m; ROI, SMART H.264+/H.265+; Bulit in Mic; IP67 protection;	

IPC 5MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.5214	DAHUA IPC-HDBW5541R-ASE 5MP IR Fixed-focal Dome WizMind Network Camera MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 5 MP (2960×1668) @25/30 fps; Built-in IR LED, and the max. illumination distance is 50 m; th deep learning algorithm, it supports: video metadata, smart sound detection, IVS, face detection, smart object detection, and people counting;	

 Ш.5215	DAHUA IPC-HFW2531S-S-S2 – Lite Series 3.6mm 5MP Lite IR Fixed-focal Bullet Network Camera 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition · Outputs 2688×1520@25/30 fps, and supports max. 5MP (2592×1944);Built-in IR LED, IR distance: 30 m; 12V DC/PoE power support ; IP67 protection grade	
 Ш.5216	DAHUA IPC-HFW2541E-S 5MP IR Fixed-focal Bullet WizSense Network Camera 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 5 MP (2592 × 1944) @20 fps, and supports 4 MP (2688 × 1520) @25/30 fps;Abnormality detection: Motion detection, video tampering, scene changing, audio detection, IP conflict, illegal access, and voltage detection	

IPC 5MP Smart-Dual Light Camera		
МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.5216	DAHUA IPC-HFW2549S-S-IL 5MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera 5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 5 MP (2960 × 1668) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps; H.265 codec, high compression rate, ultra-low bit rate; Built- in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m;	

IPC 6MP Smart-Dual Light Camera		
МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.6210	DAHUA IPC-HDW1639T-A-IL 6MP Smart Dual Light Fixed-focal Eyeball Network Camera 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 6 MP@20 fps, and supports 2688 × 1520@25/30fps;Built-in Multi-core Light, the max. IR distance is 30 m and the max. warm light distance is 30 m;	
 Ш.6211	DAHUA IPC-HFW1639TC-A-IL 6MP Smart Dual Light Fixed-focal Bullet Network Camera 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 6MP @20 fps, and supports 2688 × 1520@25/30 fps; H.265 codec, Built-in Multi-core Light, the max. IR distance is 30 m and the max. warm light distance is 30 m;	

IPC 8MP Smart-Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.8211	DAHUA IPC-HDW2849TM-S-IL 8MP Smart Dual Light Fixed-focal Eyeball WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps; Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m;	
 Ш.8212	DAHUA IPC-HFW1839TC-A-IL 8MP Entry Smart Dual Light Fixed-focal Bullet Network Camera 1/2.7" CMOS image sensor, low luminance, and high definition image; . 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520@25/30 fps; Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 30 m; Built in Mic; 12 VDC/PoE power supply, easy for installation; IP67 protection.; Supports human detection;	
 Ш.8213	DAHUA IPC-HDW1839T-A-IL 8MP Entry Smart Dual Light Fixed-focal Eyeball Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520@25/30 fps; Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 30m; Built in Mic; 12 VDC/PoE power supply, easy for installation; IP67 protection; Supports human detection;	

IPC 8MP Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.8214	DAHUA HDBW2841R-ZAS 8MP IR Vari-focal Dome WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, and the max. illumination distance is 40 m; ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments;	
 Ш.8216	DAHUA IPC-HFW2831S-S-S2 8MP Lite IR Fixed-focal Bullet Network Camera 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, max IR distance: 30 m; 12V DC/PoE power support; IP67 protection	
 Ш.8217	IPC-HFW2831T-AS-S2 3.6mm 8MP Lite IR Fixed-focal Bullet Network Camera 8MP, 1/2.7" CMOS image sensor, low illuminance, high image definition; H.265 codec, high compression rate, ultra-low bit rate; Built-in IR LED, max IR distance: 80 m; Intelligent detection: Intrusion, tripwire; Alarm: 1 in, 1 out;	
 Ш.8218	DAHUA IPC-HFW2841T-AS 8MP IR Fixed-focal Bullet WizSense Network Camera Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520@25/30 fps. Built-in IR LED, and the max. illumination distance is 80 m; Alarm: 1 in, 1 out ; audio: 1 in, 1 out ; Supports max. 256 G Micro SD card; built in MIC.	
 Ш.8219	DAHUA IPC-HFW2841T-ZAS 8MP IR Vari-focal Bullet WizSense Network Camera 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image; Built-in IR LED, and the max. illumination distance is 60 m. Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.	
 Ш.8220	DAHUA IPC-HFW2831TP-ZS – Lite Series 8MP WDR IR Bullet Network Camera 1/1.8" 8Megapixel progressive CMOS; H.265 & H.264 dual-stream encoding 25/30fps@8MP(3840×2160); WDR(120dB), Micro SD card slot, up to 128GB; 3.7~11mm motorized lens; Max IR LEDs Length 60m; IP67, IK10(optional), PoE	
 Ш.8221	DAHUA IPC-HFW3849T1-AS-PV-S3 8MP Smart Dual Illumination Active Deterrence Bullet Camera 8MP 1/2.8" CMOS image sensor, low luminance, and high definition image; Outputs max. 8 MP (3840 × 2160)@25/30 fps.; Built-in warm light and IR LED; the max. IR illumination distance is 30 m and warm light distance is 30 m; Alarm: 1 in, 1 out; audio: 1 in, 1 out;	

IPC Pan/Tilt/Zoom Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.1112	DAHUA SD4A425DB-HNY 4MP 25x Starlight IR WizSense Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ CMOS; 25x optical zoom; Starlight technology; Max. 25/30fps@4MP; IR distance up to 100m; Auto-tracking 1.0; Perimeter protection; Face detection; SMD 3.0; IP66.	
 Ш.1113	DAHUA SDT4E425-4F-GB-A-PV1 X-Spans 4MP+4MP 25x TiOC WizSense Network PTZ Camera 1/2.8" 4Megapixel F1.0 CMOS; Detail: 1/2.8" 4Megapixel STARVIS™ CMOS; 25x optical zoom; Max. 25/30fps@4M; IR distance up to 100 m; Auto tracking 3.0; Smart tracking; Perimeter protection; Active deterrence; Smart dual light +;	
 Ш.9113	DAHUA SD5A225GB-HNR 2MP 25x Starlight IR WizSense Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS; Powerful 25x optical zoom; Max.50/60fps@2M; IR distance up to 150 m; Auto Tracking 3.0; Face Detection; SMD 4.0; PoE+; IP67, IK10	
 Ш.9114	DAHUA SD5A232GB-HNR 2MP 32x Starlight IR Network PTZ Camera 1/2.8" 2Megapixel STARVIS™ CMOS; 32x optical zoom.; Starlight technology; Max.50/60fps@2M; IR distance up to 150 m; Auto-tracking 3.0; Perimeter protection; Face detection; SMD 4.0; IP67, IK10;	
 Ш.9115	DAHUA SD5A445GB-HNR 4MP 45x Starlight IR Network PTZ Camera 1/2.8" 4Megapixel STARVIS™ CMOS; 45x optical zoom; Starlight technology; Max. 25/30fps@4M; IR distance up to 150 m; Auto-tracking 3.0; Perimeter protection; Face detection; SMD 4.0; IP67, IK10;	
 Ш.1114	DAHUA SD49825GB-HNR 8MP 25x Starlight IR Network PTZ Camera 1/2.8" 8Megapixel STARVIS™ CMOS; 25x optical zoom; Starlight technology; Max. 25/30fps@8M; IR distance up to 100 m; Perimeter protection; Face detection; Quick Pick; SMD 4.0; IP66;	
 Ш.1115	DAHUA SDT4E425-8P-GB-APV1 8+4MP 25x TiOC Network Panoramic PTZ Camera Overview channel: Outputs 180° wide angle splicing image; Detail channel: 1/2.8" 4Megapixel STARVIS™ CMOS; 25x optical zoom; Max. 25/30 fps@8M; IR distance up to 100 m; Auto tracking 3.0; Smart tracking; Perimeter protection; Active deterrence; Smart dual light +;	
 Ш.1116	DAHUA IPC-PFW8802-A180 4x2MP Multi-Sensor Panoramic IR Bullet Network Camera Four 1/1.9" 2Megapixel progressive scan CMOS; H.265/H.264 triple-stream encoding; Support 180-degree panoramic view; Day/Night(ICR), 3DNR, AWB, AGC, BLC, WDR; Smart detection; Max. IR length 30m; Micro SD memory, IP67, IK10,PoE+	

IPC 2MP/4MP Wi-Fi Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.7010	DAHUA H4A 4MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera One Camera for 360° View; Human Detection; Day&Night; Auto Tracking; Two-way Talk; One-click Privacy Mode;	
 Ш.7011	DAHUA H4C 4MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera One Camera for 360° View; Human Detection; Day&Night; Auto Tracking; Two-way Talk; One-click Privacy Mode;	
 Ш.7014	DAHUA SD1A203T-GN-W – IR-15m 2MP 3x Starlight IR PTZ Wi-Fi Network Camera 1/2.8" 2Megapixel STARVIS™ CMOS , Powerful 3x optical zoom, Starlight, WDR, Max. 5/30fps@1080P, IVS, Support Wi-Fi,, IP66	

IPC 4MP Wi-Fi Full-Color Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.7017	DAHUA F4C-LED 4MP Fixed-focal Wi-Fi Full-Color Bullet Network Camera AI Human Detection; Full-color; Built-in Mic; IP67 Protection; Advanced H.265 compression technology;	

IPC 4MP/5MP Wi-Fi Smart Dual Light Camera

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.7018	DAHUA F4C-PV 4MP Fixed-focal Wi-Fi Smart Dual-Light Bullet Network Camera AI Human Detection; Smart Dual Light; Sound and Light Alarm; Two-way Talk; IP67 Protection; Advanced H.265 compression technology; Built-in warm light and IR LED, and the max. illumination distance is 30 m.	
 Ш.7121	DAHUA F2C-PV 2MP Fixed-focal Wi-Fi Bullet Network Camera AI Human Detection; Smart Dual Light; Sound and Light Alarm; Two-way Talk; IP67 Protection; Advanced H.265 compression technology; Built-in warm light and IR LED, and the max. illumination distance is 30 m.	
 Ш.7019	DAHUA P5AS-PV 5MP Outdoor Fixed-focal Wi-Fi Pan & Tilt Network Camera 5MP; Sound and Light Alarm; Red and Blue Warning Light; AI Human Detection; AI Vehicle Detection; Auto Tracking; Preset Patrol; Wi-Fi 6; One Camera for 360° View; Smart Dual Light; Bluetooth Pairing;	
 Ш.7020	DAHUA F5D-PV 5MP Outdoor Fixed-focal Wi-Fi bullet network Camera 5MP Clear images with sharp details; Sound and Light Alarm; Advanced H.265 compression technology; AI Human Detection; DMSS App Easy to use; Smart Dual Light; IP67 Protection; SD Card Low-cost storage; Wi-Fi 6	
 Ш.7120	DAHUA T5A-IL dome network Camera 5MP Clear images with sharp details; Sound and Light Alarm; Advanced H.265 compression technology; AI Human Detection; DMSS App Easy to use; Smart Dual Light; IP67 Protection; SD Card Low-cost storage; Wi-Fi 6	
 Ш.7121	DAHUA P3AE-PV 3MP Wireless Smart Dual-Light Network PT Camera Smart Dual Light; One Camera for 360° View; Sound and Light Alarm; AI Human Detection; AI Vehicle Detection; Two-way Talk; Auto Tracking; IP66 Protection;	
 Ш.7122	DAHUA P8F-PV 8MP WizColor Outdoor Wi-Fi Pan & Tilt Network Camera 4K Ultra HD, Beyond Sharpness; Sound and Light Alarm; Auto Tracking; AI Human Detection; AI Vehicle Detection; Preset Patrol; IP66 Protection; Two-way Talk; Bluetooth Pairing; Wi-Fi 6; DMSS App; H.265;	

 Ш.7123	DAHUA P3D-3F-PV-P 3+3MP Outdoor WizColor Wi-Fi Dual-Lens Pan & Tilt Camera Dual 2K; AI ISP; Linkage Tracking; Dual Channel Smart Detection; AI Human Detection; AI Vehicle Detection; Two-way Talk; IP66 Protection; Sound and Light Alarm; One Camera for 360° View; Bluetooth Pairing; Wi-Fi 6; H.265;	
 Ш.7122	DAHUA P5B-PV 5MP Outdoor Fixed-focal Wi-Fi Pan & Tilt Network Camera 360° monitoring without blind spots; Sound and Light Alarm Provides instant alarms to deter intruders; AI Human Detection; AI Vehicle Detection; Auto Tracking; Fast pairing with Bluetooth; Two-way audio;	
 Ш.7123	DAHUA P5D-5F-PV 5+5MP Outdoor Wi-Fi Dual-Lens Pan & Tilt Camera Dual Channel Smart Detection; AI Human Detection; Dual 3K; Dual-lens, Double Vision; Adjustable Dual-lens Angles; Auto Tracking; Preset Patrol; IP66 Protection; Smart Dual Light; Sound and Light Alarm; Bluetooth Pairing; Wi-Fi 6; H.265;	

Network Video Recorder

МОДЕЛ	КАРАКТЕРИСТИКИ И СПЕЦИФИКАЦИИ	ЦЕНА
 Ш.1000	DAHUA NVR2108-S3 8 Channel Smart 1U 1HDD Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264 decoding format; Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding; AI by camera: perimeter protection, and SMD Plus; Connected to the third-party network cameras · Security baseline 2.1;	
 Ш.1002	DAHUA NVR2116-S3 16 Channel Smart 1U 1HDD Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264 decoding format; Max. decoding capability: 6 × 1080p@30 fps. Supports adaptive decoding ; AI by camera: perimeter protection, and SMD Plus; Connected to the third-party network cameras; Security baseline 2.1;	
 Ш.1003	DAHUA NVR4104HS-EI 4CH Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 80 Mbps; Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	
 Ш.1011	DAHUA NVR4104HS-P-4KS3 4CH Compact 1U 4PoE 1HDD Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 8 × 1080p@30 fps or 4 × 4 MP@30 fps; Supports IP cameras with a resolution up to 12 MP; AI by Recorder supports 4-channel SMD Plus; Supports EPTZ, and one-click arming and disarming;	
 Ш.1004	DAHUA NVR4104HS-P-EI 4CH Compact 1U 4PoE 1HDD Lite Network Video Recorder Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	
 Ш.1012	DAHUA NVR4104HS-P-4KS3(960GB) 4CH Compact 1U 4PoE 1SSD 960GB Lite Network Video Recorder Comes with an internal 960GB SSD; Max. decoding capability: 8 × 1080p @30 fps or 4 × 4 MP@30 fps; Max. 80/80/60 Mbps incoming/ recording/outgoing bandwidth; Supports IP cameras with a resolution up to 12 MP; AI by Recorder supports 4-channel SMD Plus; AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, people counting, stereo analysis and heat map;	
 Ш.1005	DAHUA NVR4108HS-EI 8CH Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	
 Ш.1006	DAHUA NVR4108HS-8P-4KS3 8CH Compact 1U 8PoE 1HDD Lite Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 8 × 1080p@30 fps; Supports IP cameras with a resolution up to 12 MP; AI by Recorder supports 4-channel SMD Plus; AI by Camera supports face detection and recognition, perimeter protection;	

 Ш.1007	DAHUA NVR4108HS-8P-EI 8CH Compact 1U 8PoE 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus; AI by NVR: 1- channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus;	
--	--	---

 Ш.1008	DAHUA NVR4208-8P-4KS2/L 8 Channel 1U 2HDDs 8PoE Network Video Recorder New 4.0 user interface, Security baseline 2.1; H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch; Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding; AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD; Supports remote configuration and management of IPC, such as setting parameters	
 Ш.1009	DAHUA NVR5208-8P-4KS2E 8 Channel 1U 8PoE 4K&H.265 Pro Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264; Max 320Mbps Incoming Bandwidth; Up to 12MP Resolution for Preview and Playback; HDMI/VGA simultaneous video output; All PoE ports support ePoE & EoC; ANPR; Point of Sale (POS); Fisheye Dewarping;	
 Ш.1010	DAHUA NVR4116HS-EI 16CH Compact 1U 1HDD WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled); AI by NVR; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	
 Ш.1011	DAHUA NVR4116-8P-4KS2/L 16 Channel Smart 1U 1HDD 8PoE Network Video Recorder New 4.0 user interface, Security baseline 2.1 · H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch; Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding; Supports mainstream cameras of ONVIF and RTSP protocols; P2P remote surveillance, video play on mobile device;	
 Ш.1012	DAHUA NVR4216-16P-EI 16CH 1U 16PoE 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by NVR; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map;	

 Ш.1015	DAHUA NVR5216-8P-4KS2E 16 Channel 1U 8PoE 4K&H.265 Pro Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264 · Max 320Mbps Incoming Bandwidth · Up to 12MP Resolution for Preview and Playback; HDMI/VGA simultaneous video output; All PoE ports support ePoE & EoC; Point of Sale (POS); ANPR; Fisheye Dewarping;	
 Ш.1016	DAHUA NVR5216-16P-I 16Channel 1U 16PoE AI Network Video Recorder 16 Channel IP video access; Smart H.265+/H.265/Smart H.264+/H.264/MJPEG; Up to 16 Channel perimeter protection; Up to 4 Channel video stream face recognition; Up to 24 face pictures /sec processing; Up to 20 face databases with 100,000 face images in total; 1-8 PoE Ports support ePoE & EoC; ANPR; AI Search;	
 Ш.1017	DAHUA NVR4816-16P-4KS2/I 16 Channel 2U 16PoE 8HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG; Storage or forwarding at 256 Mbps (160 Mbps when AI function enabled); Max. decoding capability: 10 × 1080p@30 fps. Supports adaptive decoding; AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus; AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; ANPR; people counting;	

 Ш.1017	DAHUA NVR5816-R-4KS2 16 Channel 2U 4K&H.265 Pro Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG; Max 320Mbps Incoming Bandwidth; Supports RAID 0/1/5/10; Up to 12MP Resolution for Preview and Playback; 2HDMI/2VGA simultaneous video output; ANPR by Camera; Automatic Network Replenishment (ANR) Technology; Fisheye Dewarping; Smart Fan;	
 Ш.1018	DAHUA NVR4232-EI 32CH 1U 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Access, storage or forwarding at 256 Mbps ;Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding; AI by Camera: Face detection and recognition, perimeter protection;	
 Ш.1019	DAHUA NVR5232-EI2 32 Channels 1U 2HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps; Max. 384 Mbps incoming/recording/outgoing bandwidth;	
 Ш.1020	DAHUA NVR5464-EI 64 Channels 1.5U 4HDDs WizSense Network Video Recorder Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format; Max. decoding capability: or 32 × 2MP@30 fps; Max. 384 Mbps incoming/recording/outgoing bandwidth; Support AcuPick with Max. 16-Channel;	
 Ш.1021	DAHUA NVR5464-EI2 64 Channels 1.5U 4HDDs WizSense Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 40 × 1080p@30 fps or 10 × 8MP@30 fps; Max. 448/448/448 Mbps incoming/recording/outgoing bandwidth; Supports IP cameras with a resolution up to 32 MP; Supports 8K HDMI output; Supports iSCSI;	
 Ш.1022	DAHUA NVR5864-EI2 64CH 2U 8HDDs WizSense Network Video Recorder Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats; Max. decoding capability: 40 × 1080p@30 fps or 10 × 8MP@30 fps; Max. 448/448/448 Mbps incoming/recording/outgoing bandwidth; Supports IP cameras with a resolution up to 32 MP; Supports 8K HDMI output; Supports iSCSI;	